TOWN OF BOONTON

ORDINANCE NO. 09-24

A N ORDINANCE REPEALING ARTICLE II OF CHAPTER 249 AND ADOPTING NEW ARTICLE II, CHAPTER 249, "STORMWATER CONTROL", OF THE REVISED GENERAL ORDINANCES OF THE TOWN OF BOONTON TO INCLUDE NEW ARTICLES CONCERNING STORMWATER CONTROL

BE IT ORDAINED by the Town Council of the Town of Boonton, in the County of Morris and State of New Jersey, as follows:

Section 1. Article II of Chapter 249 of Revised General Ordinances of the Town of Boonton, which includes Sections 249-8 through 249-18, is hereby repealed in its entirety.

Section 2. The Revised General Ordinances of the Town of Boonton shall be amended by the inclusion of a new Article II, Chapter 249 which shall read, in its entirety, as follows:

Chapter 249

STORMWATER CONTROL

Article II

Establishment of Minimum Stormwater Management Requirements

§ 249-8. Scope and Purpose:

A. Policy Statement

Flood control, groundwater recharge, and pollutant reduction shall be achieved through the use of stormwater management measures, including green infrastructure Best Management Practices (GI BMPs) and nonstructural stormwater management strategies. GI BMPs should be utilized to meet the goal of maintaining natural hydrology to reduce stormwater runoff volume, reduce erosion, encourage infiltration and groundwater recharge, and reduce pollution. GI BMPs should be developed based upon physical site conditions and the origin, nature and the anticipated quantity, or amount, of potential pollutants. Multiple stormwater management BMPs may be necessary to achieve the established performance standards for green infrastructure, water quality, quantity, and groundwater recharge.

B. Purpose

The purpose of this Article is to establish minimum stormwater management requirements and controls for "major development," as defined in the current Stormwater Management Rules at N.J.A.C. 7:8-1.2.

- C. Applicability
- 1. This ordinance shall be applicable to the following major developments:
- i. Non-residential major developments and redevelopment projects; and
- ii. Aspects of residential major developments and redevelopment projects that are not pre-empted by the Residential Site Improvement Standards at N.J.A.C. 5:21 et seq.
- 2. This ordinance shall also be applicable to all major developments undertaken by the Town of Boonton and any other governmental entity.
- Applicability of this ordinance to major developments shall comply with last amended N.J.A.C.
 7:8-1.6, incorporated herein by reference.
- D. Compatibility with Other Permit and Ordinance Requirements

Development approvals issued pursuant to this ordinance are to be considered an integral part of development approvals and do not relieve the applicant of the responsibility to secure required permits or approvals for activities regulated by any other applicable code, rule, act, or ordinance. In their interpretation and application, the provisions of this ordinance shall be held to be the minimum requirements for the promotion of the public health, safety, and general welfare.

This ordinance is not intended to interfere with, abrogate, or annul any other ordinances, rule or regulation, statute, or other provision of law except that, where any provision of this ordinance imposes restrictions different from those imposed by any other ordinance, rule or regulation, or other provision of law, the more restrictive provisions or higher standards shall control.

For the purpose of this ordinance, the following terms, phrases, words and their derivations shall have the meanings stated herein unless their use in the text of this ordinance clearly demonstrates a different meaning. When not inconsistent with the context, words used in the present tense include the future, words used in the plural number include the singular number, and words used in the singular number include the plural number. The word "shall" is always mandatory and not merely directory. The definitions for terms used in this ordinance shall be the same as those provided in the last amended Stormwater Management Rules at N.J.A.C. 7:8-1.2, which definitions are incorporated herein by reference.

§ 249-10. Design and Performance Standards for Stormwater Management Measures

This section establishes design and performance standards for stormwater management measures for major development intended to minimize the adverse impact of stormwater runoff on water quality and water quantity and loss of groundwater recharge in receiving water bodies. Design and performance standards for stormwater management measures shall comply with last amended N.J.A.C. 7:8-5, incorporated herein by reference.

§ 249-11. Solids and Floatable Materials Control Standards

- A. Site design features identified under Section 249-10 above, or alternative designs in accordance with Section 249-10, to prevent discharge of trash and debris from drainage systems shall comply with the following standard to control passage of solid and floatable materials through storm drain inlets. For purposes of this paragraph, "solid and floatable materials" means sediment, debris, trash, and other floating, suspended, or settleable solids.
- Design engineers shall use one of the following grates whenever they use a grate in pavement or another ground surface to collect stormwater from that surface into a storm drain or surface water body under that grate:

- The New Jersey Department of Transportation (NJDOT) bicycle safe grate, which is described in Chapter 2.4 of the NJDOT Bicycle Compatible Roadways and Bikeways Planning and Design Guidelines;
- ii. A different grate, if each individual clear space in that grate has an area of no more than seven (7.0) square inches, or is no greater than 0.5 inches across the smallest dimension. Note that the Residential Site Improvement Standards at N.J.A.C. 5:21 include requirements for bicycle safe grates. Examples of grates subject to this standard include grates in grate inlets, the grate portion (non-curb-opening portion) of combination inlets, grates on storm sewer manholes, ditch grates, trench grates, and grates of spacer bars in slotted drains. Examples of ground surfaces include surfaces of roads (including bridges), driveways, parking areas, bikeways, plazas, sidewalks, lawns, fields, open channels, and stormwater system floors used to collect stormwater from the surface into a storm drain or surface water body.
- iii. For curb-opening inlets, including curb-opening inlets in combination inlets, the clear space in that curb opening, or each individual clear space if the curb opening has two or more clear spaces, shall have an area of no more than seven (7.0) square inches, or be no greater than two (2.0) inches across the smallest dimension.
- 2. The standards above do not apply:
- i. Where each individual clear space in the curb opening in existing curb-opening inlet does not have an area of more than nine (9.0) square inches;
- ii. Where the municipality agrees that the standards would cause inadequate hydraulic performance that could not practicably be overcome by using additional or larger storm drain inlets;
- iii. Where flows from the water quality design storm as specified in the last amended Stormwater Management rules at N.J.A.C. 7:8 et seq. are conveyed through any device (e.g., end of pipe netting facility, manufactured treatment device, or a catch basin hood) that is designed, at a minimum, to prevent delivery of all solid and floatable materials that could not pass through one of the following:
- a. A rectangular space four and five-eighths (4.625) inches long and one and one-half (1.5) inches wide (this option does not apply for outfall netting facilities); or

b. A bar screen having a bar spacing of 0.5 inches.

Note that these exemptions do not authorize any infringement of requirements in the Residential Site Improvement Standards for bicycle safe grates in new residential development (N.J.A.C. 5:21-4.18(b)2 and 7.4(b)1).

- iv. Where flows are conveyed through a trash rack that has parallel bars with one-inch (1 inch) spacing between the bars, to the elevation of the Water Quality Design Storm as specified in N.J.A.C. 7:8; or
- v. Where the New Jersey Department of Environmental Protection determines, pursuant to the New Jersey Register of Historic Places Rules at N.J.A.C. 7:4-7.2(c), that action to meet this standard is an undertaking that constitutes an encroachment or will damage or destroy the New Jersey Register listed historic property.

§ 249-12. Safety Standards for Stormwater Management Basins

A. This section sets forth requirements to protect public safety through the proper design and operation of stormwater management basins. This section applies to any new stormwater management basin. Safety standards for stormwater management measures shall comply with last amended N.J.A.C. 7:8-6, incorporated herein by reference.

B. Safety Ledge Illustration

Elevation View –Basin Safety Ledge Configuration Safety Ledge, 4 to 6 feet in Width, Gently Sloped for Drainage Top of Ledge, 12 to 18 inches Permanent Above Water Surface Water Level Top of Ledge, 30 inches Below Safety Ledge, Water 4 to 6 feet in Width, Surface Gently Sloped for Drainage Stable Slope Only For Basins with Permanent Pool of Water Not to Scale

§ 249-13. Requirements for a Site Development Stormwater Plan

- A. Submission of Site Development Stormwater Plan
- 1. Whenever an applicant seeks municipal approval of a development subject to this ordinance, the applicant shall submit all of the required components of the Checklist for the Site Development Stormwater Plan in Subsection C below as part of the submission of the application for approval.
- 2. The applicant shall demonstrate that the project meets the standards set forth in this ordinance.
- 3. The applicant shall submit twelve copies of the materials listed in the checklist for site development stormwater plans in accordance with Subsection C of this Section.
- B. Site Development Stormwater Plan Approval

The applicant's Site Development project shall be reviewed as a part of the review process by the municipal board or official from which municipal approval is sought. That municipal board or official shall consult the municipality's review engineer to determine if all of the checklist requirements have been satisfied and to determine if the project meets the standards set forth in this ordinance.

C. Submission of Site Development Stormwater Plan

The following information shall be required:

1. Topographic Base Map

The reviewing engineer may require upstream tributary drainage system information as necessary. It is recommended that the topographic base map of the site be submitted which extends a minimum of 200 feet beyond the limits of the proposed development, at a scale of 1"=200' or greater, showing 2-foot contour intervals. The map as appropriate may indicate the following: existing surface water drainage, shorelines, steep slopes, soils, erodible soils, perennial or intermittent streams that drain into or upstream of the Category One waters, wetlands and flood plains along with their appropriate buffer strips, marshlands and other wetlands, pervious or vegetative surfaces, existing man-made structures, roads, bearing and distances of property lines, and significant natural and manmade features not otherwise shown.

2. Environmental Site Analysis

A written and graphic description of the natural and man-made features of the site and its surroundings should be submitted. This description should include a discussion of soil conditions, slopes, wetlands, waterways and vegetation on the site. Particular attention should be given to unique, unusual, or environmentally sensitive features and to those that provide particular opportunities or constraints for development.

3. Project Description and Site Plans

A map (or maps) at the scale of the topographical base map indicating the location of existing and proposed buildings roads, parking areas, utilities, structural facilities for stormwater management and sediment control, and other permanent structures. The map(s) shall also clearly show areas where alterations will occur in the natural terrain and cover, including lawns and other landscaping, and seasonal high groundwater elevations. A written description of the site plan and justification for proposed changes in natural conditions shall also be provided.

4. Land Use Planning and Source Control Plan

This plan shall provide a demonstration of how the goals and standards as set forth within this section are being met. The focus of this plan shall be to describe how the site is being developed to meet the objective of controlling groundwater recharge, stormwater quality and stormwater quantity problems at the source by land management and source controls whenever possible.

5. Stormwater Management Facilities Map

The following information, illustrated on a map of the same scale as the topographic base map, shall be included:

- i. Total area to be disturbed, paved or built upon, proposed surface contours, land area to be occupied by the stormwater management facilities and the type of vegetation thereon, and details of the proposed plan to control and dispose of stormwater.
- ii. Details of all stormwater management facility designs, during and after construction, including discharge provisions, discharge capacity for each outlet at different levels of detention and emergency spillway provisions with maximum discharge capacity of each spillway.

Calculations

- i. Comprehensive hydrologic and hydraulic design calculations for the pre-development and postdevelopment conditions for the design storms as specific within this ordinance.
- ii. When the proposed stormwater management control measures depend on the hydrologic properties of soils or require certain separation from the seasonal highwater table, then a soils report shall be submitted. The soils report shall be based on onsite boring logs or soil pit profiles. The number and location of required soil borings or soil pits shall be determined based on what is needed to determine the suitability and distribution of soils present at the location of the control measure.

7. Maintenance and Repair Plan

The design and planning of the stormwater management facility shall meet the maintenance requirements as set forth within this section.

8. Waiver from Submission Requirements

The municipal official or board reviewing an application under this ordinance may, in consultation with the municipality's review engineer, waive submission of any of the requirements of this ordinance when it can be demonstrated that the information requested is impossible to obtain or it would create a hardship on the applicant to obtain and its absence will not materially affect the review process.

§ 249-14. Maintenance and Repair

A. Applicability

All applicable projects subject to review pursuant to ordinance, shall comply with the following additional requirements:

- B. General Maintenance
- 1. Maintenance for stormwater management measures shall comply with last amended N.J.A.C. 7:8-5.8, incorporated herein by reference.
- 2. Maintenance responsibility and maintenance guarantee.
- i. If the maintenance plan identifies a person other than the property owner (for example, a developer, a public agency or homeowners' association) as having the responsibility for maintenance, the plan shall

include documentation of such person's or entity's agreement to assume this responsibility, or of the owner's obligation to dedicate a stormwater management facility to such person under an applicable ordinance or regulation; and

- ii. Responsibility for maintenance shall not be assigned or transferred to the owner or tenant of an individual property in a residential development or project, unless such owner or tenant owns or leases the entire residential development or project. The individual property owner may be assigned incidental tasks, such as weeding of a green infrastructure BMP, provided the individual agrees to assume these tasks; however, the individual cannot be legally responsible for all of the maintenance required.
- iii. The posting of a two-year maintenance guarantee is required in accordance with N.J.S.A. 40:55D-53. The guarantee shall be posted with the Town. Maintenance and inspection guidance can be found on the NJDEP website at: https://www.njstormwater.org/maintenance_guidance.htm.
- 3. In the event that the stormwater management facility is determined by the Town Engineer or a designee to be danger to public safety or public health, or if it is determined to be in need of maintenance or repair, the Town Engineer or a designee shall so notify the responsible person in writing. Upon receipt of that notice, the responsible person shall have fourteen (14) days to effect maintenance and repair of the facility in a manner that is approved by the municipal engineer or a designee. The Town Engineer, in his or her discretion, may extend the time allowed for effecting maintenance and repair for good cause. If the responsible person fails or refuses to perform such maintenance and repair, the Town may, but is not required to, proceed to do so and shall bill the cost thereof to the responsible person. Nonpayment of such bill shall constitute a lien on the property.
- C. Nothing in this subsection shall preclude the Planning Board or the Town from requiring the posting of a performance or maintenance guarantee in accordance with N.J.S.A. 40:55D-53.

§ 249-15. Penalties

A. Fines.

- Any violation of any provision of this chapter shall be punishable as provided in Section 300-121,
 Article XXIV, General Administration and Enforcement, of the Code of the Town of Boonton. The
- following individuals shall be subject to potential punishment:
- a. The owner, general agent, contractor or occupant of a building, premises or part thereof where such a violation has been committed or does exist; and
- b. Any agent, contractor, architect, engineer, builder, corporation or other person who commits, takes part or assists in the violation.
- 2. Each day that a violation continues shall constitute a separate and distinct offense.
- 3. The imposition of penalties herein shall not preclude the municipality or any other person from instituting an action to prevent an unlawful construction, reconstruction, alteration, repair, conversion, or use, or to restrain, correct or abate a violation, or to prevent the illegal occupancy of a building, land or premises.
- B. Injunctive relief. In addition to the foregoing, the municipality may institute an action for injunctive relief.

§ 249-16. Severability

Each section, subsection, sentence, clause, and phrase of this Ordinance is declared to be an independent section, subsection, sentence, clause, and phrase, and finding or holding of any such portion of this Ordinance to be unconstitutional, void, or ineffective for any cause or reason shall not affect any other portion of this Ordinance.

- **§ 249-17.** All Ordinances or parts of Ordinances which are inconsistent herewith are hereby repealed to the extent of such inconsistency.
- § 249-18. This Ordinance shall take effect immediately after final passage and publication in the manner provided by law.

INTRODUCED:	April 15, 2024	Mayor and Town Council of the Town of Boonton in the County of Morris and State of New Jersey
ADOPTED:	May 6, 2024	
ATTEST:		By: James Lynch, Mayor
Elizabeth Bonsiewich. Town Clerk		