

**ORDINANCE FOR ADOPTION OF THE FLOODPLAIN MANAGEMENT REGULATIONS  
OF THE TOWNSHIP OF LONG BEACH**

**ORDINANCE NO. 21-32C**

**AN ORDINANCE BY THE BOARD OF COMMISSIONERS AMENDING THE TOWNSHIP OF LONG BEACH CODE OF ORDINANCES TO REPEAL CHAPTER 94; TO ADOPT FLOOD HAZARD MAPS; TO DESIGNATE A FLOODPLAIN ADMINISTRATOR; AND PROVIDING FOR SEVERABILITY AND AN EFFECTIVE DATE.**

---

**WHEREAS**, the Legislature of the State of New Jersey has, in N.J.S.A. 40:48 et seq and N.J.S.A. 40:55D et seq., conferred upon local governments the authority to adopt regulations designed to promote the public health, safety, and general welfare of its citizenry; and

**WHEREAS**, the Federal Emergency Management Agency has identified special flood hazard areas within the boundaries of the Township of Long Beach and such areas may be subject to periodic inundation which may result in loss of life and property, health and safety hazards, disruption of commerce and governmental services, extraordinary public expenditures for flood protection and relief, and impairment of the tax base, all of which adversely affect the public health, safety and general welfare, and

**WHEREAS**, The Township of Long Beach was accepted for participation in the National Flood Insurance Program on May 26, 1970 and the Board of Commissioners desires to continue to meet the requirements of Title 44 Code of Federal Regulations, Sections 59, 60, 65, and 70 necessary for such participation; and

**WHEREAS**, The Township of Long Beach is required, pursuant to N.J.S.A. 5:23 et seq., to administer and enforce the State building codes, and such building codes contain certain provisions that apply to the design and construction of buildings and structures in flood hazard areas; and

**WHEREAS**, the Township of Long Beach is required, pursuant to N.J.S.A. 40:49-5, to enforce zoning codes that secure safety from floods and contain certain provisions that apply to the development of lands; and

**WHEREAS**, the Township of Long Beach is required, pursuant to N.J.S.A.58:16A-57, within 12 months after the delineation of any flood hazard area, to adopt rules and regulations concerning the development and use of land in the flood fringe area which at least conform to the standards promulgated by the New Jersey Department of Environmental Protection (NJDEP).

**NOW, THEREFORE, BE IT ORDAINED** by the Board of Commissioners of the Township of Long Beach that the following floodplain management regulations are hereby adopted.

**SECTION 1. RECITALS.**

The foregoing whereas clauses are incorporated herein by reference and made a part hereof.

**SECTION 2.** These regulations specifically repeal and replace the following ordinance(s) and regulation(s): Chapter 94, Flood Damage Prevention. **Chapter 94 of the Township Code, Flood Damage Prevention, shall read in its entirety as follows:**

### **SECTION 94-1 SCOPE AND ADMINISTRATION**

**94-1.1 Title.** These regulations, in combination with the flood provisions of the Uniform Construction Code (UCC) N.J.A.C. 5:23 (hereinafter "Uniform Construction Code," consisting of the Building Code, Residential Code, Rehabilitation Subcode, and related codes, and the New Jersey Flood Hazard Area Control Act (hereinafter "FHACA"), N.J.A.C. 7:13, shall be known as the *Floodplain Management Regulations* of the Township of Long Beach (hereinafter "these regulations").

**94-1.2 Scope.** These regulations, in combination with the flood provisions of the Uniform Construction Code and FHACA shall apply to all proposed development in flood hazard areas established in Section 94-2 of these regulations.

**94-1.3 Purposes and objectives.** The purposes and objectives of these regulations are to promote the public health, safety and general welfare and to minimize public and private losses due to flood conditions in specific flood hazard areas through the establishment of comprehensive regulations for management of flood hazard areas, designed to:

- (1) Protect human life and health.
- (2) Prevent unnecessary disruption of commerce, access, and public service during times of flooding.
- (3) Manage the alteration of natural floodplains, stream channels and shorelines;
- (4) Manage filling, grading, dredging and other development which may increase flood damage or erosion potential.
- (5) Prevent or regulate the construction of flood barriers which will divert floodwater or increase flood hazards.
- (6) Contribute to improved construction techniques in the floodplain.
- (7) Minimize damage to public and private facilities and utilities.
- (8) Help maintain a stable tax base by providing for the sound use and development of flood hazard areas.
- (9) Minimize the need for rescue and relief efforts associated with flooding.
- (10) Ensure that property owners, occupants, and potential owners are aware of property located in flood hazard areas.
- (11) Minimize the need for future expenditure of public funds for flood control

projects and response to and recovery from flood events.

- (12) Meet the requirements of the National Flood Insurance Program for community participation set forth in Title 44 Code of Federal Regulations, Section 59.22.

**94-1.4 Coordination with Building Codes.** Pursuant to the requirement established in N.J.A.C. 5:23, the Uniform Construction Code, that the Township of Long Beach administer and enforce the State building codes, the Board of Commissioners of the Township of Long Beach does hereby acknowledge that the Uniform Construction Code contains certain provisions that apply to the design and construction of buildings and structures in flood hazard areas. Therefore, these regulations are intended to be administered and enforced in conjunction with the Uniform Construction Code.

**94-1.5 Ordinary Building Maintenance and Minor Work.** Improvements defined as ordinary building maintenance and minor work projects by the Uniform Construction Code including non-structural replacement-in-kind of windows, doors, cabinets, plumbing fixtures, decks, walls, partitions, new flooring materials, roofing, etc. shall be evaluated by the Floodplain Administrator through the floodplain development permit to ensure compliance with the Substantial Damage and Substantial Improvement Section 94-3.14 of this ordinance.

**94-1.6 Warning.** The degree of flood protection required by these regulations is considered reasonable for regulatory purposes and is based on scientific and engineering considerations. Larger floods can and will occur. Flood heights may be increased by man-made or natural causes. Enforcement of these regulations does not imply that land outside the special flood hazard areas, or that uses permitted within such flood hazard areas, will be free from flooding or flood damage.

**94-1.7 Other laws.** The provisions of these regulations shall not be deemed to nullify any provisions of local, State, or Federal law.

**94-1.8 Violations and Penalties for Noncompliance.** No structure or land shall hereafter be constructed, re-located to, extended, converted, or altered without full compliance with the terms of this ordinance and other applicable regulations. Violation of the provisions of this ordinance by failure to comply with any of its requirements (including violations of conditions and safeguards established in connection with conditions) shall constitute a violation under N.J.S.A. 40:49-5. Any person who violates this ordinance or fails to comply with any of its requirements shall be subject to one (1) or more of the following: a fine of not more than \$1,000, imprisonment for a term not exceeding one 90 days or a period of community service not exceeding 90 days.

Each day in which a violation of an ordinance exists shall be considered to be a separate and distinct violation subject to the imposition of a separate penalty for each day of the violation as the Court may determine except that the owner will be afforded the opportunity to cure or abate the condition during a 30-day period and shall be afforded the opportunity for a hearing before the court for an independent determination concerning the violation. Subsequent to the expiration of the 30-day period, a fine greater than \$1250 may be imposed if the court has not determined otherwise, or if upon reinspection of the property, it is determined that the abatement has not been substantially completed.

Any person who is convicted of violating an ordinance within one year of the date of a previous violation of the same ordinance and who was fined for the previous violation, shall be sentenced by a court to an additional fine as a repeat offender. The additional fine imposed by the court upon a person for a repeated offense shall not be less than the minimum or exceed the maximum fine fixed for a violation of the ordinance, but shall be calculated separately from the fine imposed for the violation of the ordinance.

**94-1.8.1 Solid Waste Disposal in a Flood Hazard Area.** Any person who has unlawfully disposed of solid waste in a floodway or floodplain who fails to comply with this ordinance or fails to comply with any of its requirements shall upon conviction thereof be fined not more than \$2500 or up to a maximum penalty by a fine not exceeding \$10,000 under N.J.S.A. 40:49-5.

**94-1.9 Abrogation and greater restrictions.** These regulations supersede any ordinance in effect in flood hazard areas. However, these regulations are not intended to repeal or abrogate any existing ordinances including land development regulations, subdivision regulations, zoning ordinances, stormwater management regulations, or building codes. In the event of a conflict between these regulations and any other ordinance, code, or regulation, the more restrictive shall govern.

## SECTION 94-2 APPLICABILITY

**94-2.1 General.** These regulations, in conjunction with the Uniform Construction Code, provide minimum requirements for development located in flood hazard areas, including the subdivision of land and other developments; site improvements and installation of utilities; placement and replacement of manufactured homes; placement of recreational vehicles; new construction and alterations, repair, reconstruction, rehabilitation or additions of existing buildings and structures; substantial improvement of existing buildings and structures, including repair of substantial damage; installation of tanks; temporary structures and temporary or permanent storage; utility and miscellaneous Group U buildings and structures; and certain building work exempt from permit under the Uniform Construction Code; and other buildings and development activities.

**94-2.2 Establishment of Flood Hazard Areas.** The Township of Long Beach was accepted for participation in the National Flood Insurance Program on May 26, 1970.

The National Flood Insurance Program (NFIP) floodplain management regulations encourage that all Federal, State, and Local regulations that are more stringent than the minimum NFIP standards take precedence in permitting decisions. The FHACA requires that the effective Flood Insurance Rate Map, most recent preliminary FEMA mapping and flood studies, and Department delineations be compared to determine the most restrictive mapping. The FHACA also regulates unstudied flood hazard areas in watersheds measuring 50 acres or greater in size and most riparian zones in New Jersey. Because of these higher standards, the regulated flood hazard area in New Jersey may be more expansive and more restrictive than the FEMA Special Flood Hazard Area. Maps and studies that establish flood hazard areas are on file at the Long Beach Township Municipal Building, 6805 Long Beach Boulevard, Brant Beach, New Jersey 08008-3661.

The following sources identify flood hazard areas in this jurisdiction and must be considered when determining the Best Available Flood Hazard Data Area:

- 1) **Effective Flood Insurance Study.** Special Flood Hazard Areas (SFHAs) identified by the Federal Emergency Management Agency in a scientific and engineering report entitled Flood Insurance Study, Ocean County, New Jersey (All Jurisdictions) dated September 26, 2006, revised on June 20, 2018, and December 16, 2021, and the accompanying Flood Insurance Rate Maps (FIRM) identified in Table 94-2.2(1) whose effective date is September 26, 2006 are hereby adopted by reference.

Table 94-2.2(1)

Map Panel #	Effective Date	Revision Letter	Map Panel #	Effective Date	Revision Letter
34029CIND1	12/16/2021	C	34029C0518	12/16/2021	G
34029CIND2	12/16/2021	C	34029C0526	09/29/2006	F
34029C0419	09/29/2006	F	34029C0584	09/29/2006	F
34029C0438	09/29/2006	F	34029C0592	09/29/2006	F
34029C0507	09/29/2006	F	34029C0593	09/29/2006	F
34029C0508	12/16/2021	G	34029C0594	09/29/2006	F
34029C0509	12/16/2021	G	34029C0601	09/29/2006	F
34029C0513	12/16/2021	G	34029C0602	09/29/2006	F
34029C0514	12/16/2021	G	34029C0603	09/29/2006	F
34029C0516	12/16/2021	G	34029C0604	09/29/2006	F
34029C0517	09/29/2006	F	34029C0611	09/29/2006	F
34029C0660	09/29/2021	F	34029C0582	09/29/2006	F
34029C0418	09/29/2006	F			

- 2) **Federal Best Available Information.** The Township of Long Beach shall utilize Federal flood information as listed in the table below that provides more detailed hazard information, higher flood elevations, larger flood hazard areas, and results in more restrictive regulations. This information may include but is not limited to preliminary flood elevation guidance from FEMA (such as Advisory Flood Hazard Area Maps, Work Maps or Preliminary FIS and FIRM). Additional Federal Best Available studies issued after the date of this ordinance must also be considered. These studies are listed on FEMA's Map Service Center. This information shall be used for floodplain regulation purposes only.

Table 94-2.2(2)

Map Panel #	Preliminary Date	Map Panel #	Preliminary Date
34029C0418G	3/28/2014	34029C0592G	3/28/2014
34029C0419G	3/28/2014	34029C0593G	3/28/2014
34029C0438G	1/30/2015	34029C0594G	3/28/2014
34029C0507G	1/30/2015	34029C0601G	3/28/2014
34029C0517G	1/30/2015	34029C0602G	3/28/2014
34029C0526G	3/28/2014	34029C0603G	1/30/2015
34029C0582G	3/28/2014	34029C0604G	3/28/2014
34029C0584G	3/28/2014	34029C0660G	3/28/2014

34029C0508H	3/28/2014	34029C0514H	1/30/2015
34029C0509H	1/30/2015	34029C0516H	3/28/2014
34029C0513H	3/28/2014	34029C0518H	1/30/2015

- 3) Flood Hazard Protection Area – Primary Frontal Dune (PFD)  
 The Township of Long Beach hereby designates all lands in the Primary Frontal Dune area which are designated as AO, Unshaded X, and Shaded X as a Flood Hazard Protection Area – Primary Frontal Dune (FHPA - PFD) after considering the most restrictive of the effective Flood Insurance Study and other Federal Best Available Information described in Section 94-2.2 and any requirements for determining flood hazard areas as specified in N.J.A.C. 7:13. This FHPA is designated because of the erodibility of the underlying soil characteristics and the vulnerability of structures in these areas to erosion and scour if dunes and/or flood protection infrastructure seaward of these areas are breached
  
- 4) Flood Hazard Protection Area A  
 Flood Hazard Protection Area A - The Township of Long Beach hereby designates all lands designated as AE 7 or less and any AO Zones not located within a Primary Frontal Dune area which specify elevations above ground surface that result in Local Design Flood Elevations less than 8 feet not including freeboard as a Flood Hazard Protection Area A (FHPA - A) after considering the most restrictive of the effective Flood Insurance Study and other Federal Best Available Information described in Section 94-2.2 and any requirements for determining flood hazard areas as specified in N.J.A.C. 7:13.. This FHPA is designated because of the erodibility of the underlying soil characteristics and the vulnerability of structures in these areas to erosion and scour if dunes and/or flood protection infrastructure in these areas are breached.
  
- 5) Flood Hazard Protection Area V  
 The Township of Long Beach hereby designates all lands designated as VE 9 as a Flood Hazard Protection Area V (FHPA - V) after considering the most restrictive of the effective Flood Insurance Study and other Federal Best Available Information described in Section 94-2.2 and any requirements for determining flood hazard areas as specified in N.J.A.C. 7:13. This FHPA is designated because of the erodibility of the underlying soil characteristics and the vulnerability of structures in these areas to erosion and scour if dunes and/or flood protection infrastructure in these areas are breached.
  
- 6) Flood Hazard Protection Area X  
 The Township of Long Beach hereby designates all lands designated as X Zones on the June 17, 2013 FIRM Map or any subsequent map and which are not located in the Primary Frontal Dune Area as a Flood Hazard Protection Area X (FHPA - X) after considering the most restrictive of the effective Flood Insurance Study and other Federal Best Available Information described in Section 94-2.2 and any requirements for determining flood hazard areas as specified in N.J.A.C. 7:13. This FHPA is designated because of the erodibility of

the underlying soil characteristics and the vulnerability of structures in these areas to erosion and scour if dunes and/or flood protection infrastructure in these areas are breached.

- 7) **Other Best Available Data.** The Township of Long Beach shall utilize high water elevations from flood events, groundwater flooding areas, studies by federal or state agencies, or other information deemed appropriate by the Township of Long Beach. Other “best available information” may not be used which results in less restrictive flood elevations, design standards, or smaller flood hazard areas than the sources described in Section 94-2.2 (1) and (2), above. This information shall be used for floodplain regulation purposes only.

### **94-2.3 Establishing the Local Design Flood Elevation (LDFE).**

The Local Design Flood Elevation (LDFE) is established in the flood hazard areas determined in Section 94-2.2, above, using the best available flood hazard data sources, and the Flood Hazard Area Control Act minimum Statewide elevation requirements for lowest floors in A, Coastal A, and V zones, ASCE 24 requirements for critical facilities as specified by the building code, plus additional freeboard as specified by this ordinance. At a minimum, the Local Design Flood Elevation shall be as follows:

- 1) For a delineated watercourse, the elevation associated with the Best Available Flood Hazard Data Area determined in Section 94-2.2, above plus one foot or as described by N.J.A.C. 7:13 of freeboard; or
- 2) AO Zones – For Zone AO areas on the municipality’s FIRM (or on preliminary flood elevation guidance from FEMA) unless located within the Flood Hazard Protection Area - Primary Frontal Dunes or a Flood Hazard Protection Area - A, the Local Design Flood Elevation is determined from the FIRM panel as the highest adjacent grade plus the depth number specified plus one foot of freeboard. If no depth number is specified, the Local Design Flood Elevation is three (3) feet above the highest adjacent grade.
- 3) Flood Hazard Protection Area – Primary Frontal Dune – For FHPA-PFD areas designated in 94-2.2 in the Primary Frontal Dune, no building or structure shall be erected or enlarged which has the lowest primary floor level elevated less than 21 feet nor more than 28 feet above the mean sea level as determined by the 1988 North American Vertical Datum. In no case shall the Local Design Flood Elevation in this area be lower than required by 94-2.3(1) or the elevation required by any State Coastal Zone Management permit,
- 4) Flood Hazard Protection Area – A – For FHPA-A areas designated in 94-2.2 with mapped elevations AE 7 or less and any mapped AO Zones not located within a Primary Frontal Dune area which specify elevations above ground surface that result in Local Design Flood Elevations less than 8 feet not including freeboard, the Local Design Flood Elevation shall be 8 feet NAVD88 plus one foot of freeboard.

In no case shall the Local Design Flood Elevation in this area be lower than required by 94-2.3(1).

- 5) Flood Hazard Protection Area – V - For FHPA-V areas designated in 94-2.2 with mapped with mapped elevations VE 9 or less, the Local Design Flood Elevation on shall be 10 feet NAVD88 plus one foot of freeboard. In no case shall the Local Design Flood Elevation in this area be lower than required by 94-2.3(1).
- 6) Flood Hazard Protection Area – X - For FHPA-X areas designated in 94-2.2 with mapped X zones not in the Primary Frontal Dune Area, the Local Design Flood Elevation shall be the same as the nearest AE Zone elevation plus one foot of freeboard provided that that AE zone elevation is no lower than eight feet not including the required one foot of freeboard. In no case shall the Local Design Flood Elevation in this area be lower than required by 94-2.3(1).
- 7) Class IV Critical Facilities - For any proposed development of new and substantially improved Flood Design Class IV Critical Facilities, the Local Design Flood Elevation must be the higher of the 0.2% annual chance (500 year) flood elevation or the Flood Hazard Area Design Flood Elevation with an additional 2 feet of freeboard in accordance with ASCE 24.
- 8) Class III Critical Facilities - For proposed development of new and substantially improved Flood Design Class III Critical Facilities in coastal high hazard areas, the Local Design Flood Elevation must be the higher of the 0.2% annual chance (500 year) flood elevation or the Flood Hazard Area Design Flood Elevation with an additional 1 foot of freeboard in accordance with ASCE 24.

### **SECTION 94-3 DUTIES AND POWERS OF THE FLOODPLAIN ADMINISTRATOR**

**94-3.1 Floodplain Administrator Designation.** The Code Enforcement Officer is designated the Floodplain Administrator. The Floodplain Administrator shall have the authority to delegate performance of certain duties to other employees.

**94-3.2 General.** The Floodplain Administrator is authorized and directed to administer the provisions of these regulations. The Floodplain Administrator shall have the authority to render interpretations of these regulations consistent with the intent and purpose of these regulations and to establish policies and procedures in order to clarify the application of its provisions. Such interpretations, policies and procedures shall be consistent with the intent and purpose of these regulations and the flood provisions of the building code and shall not have the effect of waiving specific requirements without the granting of a variance pursuant to Section 94-7 of these regulations.

**94-3.3 Coordination.** The Floodplain Administrator shall coordinate with the Construction Official to administer and enforce the flood provisions of the Uniform Construction Code.

**94-3.4 Duties.** The duties of the Floodplain Administrator shall include but are not



limited to:

- (1) Review all permit applications to determine whether proposed development is located in flood hazard areas established in Section 94-2 of these regulations.
- (2) Require development in flood hazard areas to be reasonably safe from flooding and to be designed and constructed with methods, practices and materials that minimize flood damage.
- (3) Interpret flood hazard area boundaries and provide available flood elevation and flood hazard information.
- (4) Determine whether additional flood hazard data shall be obtained or developed.
- (5) Review required certifications and documentation specified by these regulations and the building code to determine that such certifications and documentations are complete.
- (6) Establish, in coordination with the Construction Official, written procedures for administering and documenting determinations of substantial improvement and substantial damage made pursuant to Section 94-3.14 of these regulations.
- (7) Coordinate with the Construction Official and others to identify and investigate damaged buildings located in flood hazard areas and inform owners of the requirement to obtain permits for repairs.
- (8) Review requests submitted to the Construction Official seeking approval to modify the strict application of the flood load and flood resistant construction requirements of the Uniform Construction code to determine whether such requests require consideration as a variance pursuant to Section 94-7 of these regulations.
- (9) Require applicants who submit hydrologic and hydraulic engineering analyses to support permit applications to submit to FEMA the data and information necessary to maintain the Flood Insurance Rate Maps when the analyses propose to change base flood elevations, flood hazard area boundaries, or floodway designations; such submissions shall be made within 6 months of such data becoming available.
- (10) Require applicants who propose alteration of a watercourse to notify adjacent jurisdictions and the NJDEP Bureau of Flood Engineering, and to submit copies of such notifications to the Federal Emergency Management Agency (FEMA).
- (11) Inspect development in accordance with Section 94-6 of these regulations and inspect flood hazard areas to determine if development is undertaken without issuance of permits.

- (12) Prepare comments and recommendations for consideration when applicants seek variances in accordance with Section 94-7 of these regulations.
- (13) Cite violations in accordance with Section 94-8 of these regulations.
- (14) Notify the Federal Emergency Management Agency when the corporate boundaries of the Township of Long Beach have been modified.
- (15) Permit Ordinary Maintenance and Minor Work in the regulated areas discussed in Section 94-2.2.

**94-3.5 Use of changed technical data.** The Floodplain Administrator and the applicant shall not use changed flood hazard area boundaries or base flood elevations for proposed buildings or developments unless the Floodplain Administrator or applicant has applied for a Conditional Letter of Map Revision (CLOMR) to the Flood Insurance Rate Map (FIRM) revision and has received the approval of the Federal Emergency Management Agency. A revision of the effective FIRM does not remove the related feature(s) on a flood hazard area delineation that has been promulgated by the NJDEP. A separate application must be made to the State pursuant to N.J.A.C. 7:13 for revision of a flood hazard design flood elevation, flood hazard area limit, floodway limit, and/or other related feature.

**94-3.6 Other permits.** It shall be the responsibility of the Floodplain Administrator to assure that approval of a proposed development shall not be given until proof that necessary permits have been granted by Federal or State agencies having jurisdiction over such development, including section 404 of the Clean Water Act. In the event of conflicting permit requirements, the Floodplain Administrator must ensure that the most restrictive floodplain management standards are reflected in permit approvals.

**94-3.7 Determination of Local Design Flood Elevations.** If design flood elevations are not specified, the Floodplain Administrator is authorized to require the applicant to:

- (1) Obtain, review, and reasonably utilize data available from a Federal, State, or other source, or
- (2) Determine the design flood elevation in accordance with accepted hydrologic and hydraulic engineering techniques. Such analyses shall be performed and sealed by a licensed professional engineer. Studies, analyses, and computations shall be submitted in sufficient detail to allow review and approval by the Floodplain Administrator. The accuracy of data submitted for such determination shall be the responsibility of the applicant.

It shall be the responsibility of the Floodplain Administrator to verify that the applicant's proposed Best Available Flood Hazard Data Area and the Local Design Flood Elevation in any development permit accurately applies the best available flood hazard data and methodologies for determining flood hazard areas and design elevations described in 94-2.2 and 94-2.3 respectively. This information shall be provided to the Construction Official

and documented according to Section 94-3.15.

**94-3.8 Requirement to submit new technical data.** Base Flood Elevations may increase or decrease resulting from natural changes (e.g., erosion, accretion, channel migration, subsidence, uplift) or man-made physical changes (e.g. dredging, filling, excavation) affecting flooding conditions. As soon as practicable, but not later than six months after the date of a man-made change or when information about a natural change becomes available, the Floodplain Administrator shall notify the Federal Insurance Administrator of the changes by submitting technical or scientific data in accordance with Title 44 Code of Federal Regulations Section 65.3. Such a submission is necessary so that upon confirmation of those physical changes affecting flooding conditions, risk premium rates and floodplain management requirements will be based upon current data.

**94-3.9 Activities in riverine flood hazard areas.** In riverine flood hazard areas where design flood elevations are specified but floodways have not been designated, the Floodplain Administrator shall not permit any new construction, substantial improvement or other development, including the placement of fill, unless the applicant submits an engineering analysis prepared by a licensed professional engineer that demonstrates that the cumulative effect of the proposed development, when combined with all other existing and anticipated flood hazard area encroachment, will not increase the design flood elevation more than 0.2 feet at any point within the community.

**94-3.10 Floodway encroachment.** Prior to issuing a permit for any floodway encroachment, including fill, new construction, substantial improvements and other development or land- disturbing-activity, the Floodplain Administrator shall require submission of a certification prepared by a licensed professional engineer, along with supporting technical data, that demonstrates that such development will not cause any increase in the base flood level.

**94-3.10.1 Floodway revisions.** A floodway encroachment that increases the level of the base flood is authorized if the applicant has applied for a Conditional Letter of Map Revision (CLOMR) to the Flood Insurance Rate Map (FIRM) and has received the approval of FEMA.

**94-3.11 Watercourse alteration.** Prior to issuing a permit for any alteration or relocation of any watercourse, the Floodplain Administrator shall require the applicant to provide notification of the proposal to the appropriate authorities of all adjacent government jurisdictions, as well as the NJDEP Bureau of Flood Engineering and the Division of Land Resource Protection. A copy of the notification shall be maintained in the permit records and submitted to FEMA.

**94-3.11.1 Engineering analysis.** The Floodplain Administrator shall require submission of an engineering analysis prepared by a licensed professional engineer, demonstrating that the flood-carrying capacity of the altered or relocated portion of the watercourse will be maintained, neither increased nor decreased. Such watercourses shall be maintained in a manner that preserves the channel's flood-carrying capacity.

**94-3.12 Alterations in coastal areas.** The excavation or alteration of sand dunes is governed by the New Jersey Coastal Zone Management (CZM) rules, N.J.A.C. 7:7.

Prior to issuing a flood damage prevention permit for any alteration of sand dunes in coastal high hazard areas and Coastal A Zones, the Floodplain Administrator shall require that a New Jersey CZM permit be obtained and included in the flood damage prevention permit application. The applicant shall also provide documentation of any engineering analysis, prepared by a licensed professional engineer, that demonstrates that the proposed alteration will not increase the potential for flood damage.

**94-3.13 Development in riparian zones** All development in Riparian Zones as described in N.J.A.C. 7:13 is prohibited by this ordinance unless the applicant has received an individual or general permit or has complied with the requirements of a permit by rule or permit by certification from NJDEP Division of Land Resource Protection prior to application for a floodplain development permit and the project is compliant with all other Floodplain Development provisions of this ordinance. The width of the riparian zone can range between 50 and 300 feet and is determined by the attributes of the waterbody and designated in the New Jersey Surface Water Quality Standards N.J.A.C. 7:9B. The portion of the riparian zone located outside of a regulated water is measured landward from the top of bank. Applicants can request a verification of the riparian zone limits or a permit applicability determination to determine State permit requirements under N.J.A.C. 7:13 from the NJDEP Division of Land Resource Protection.

**94-3.14 Substantial improvement and substantial damage determinations.** When buildings and structures are damaged due to any cause including but not limited to man-made, structural, electrical, mechanical, or natural hazard events, or are determined to be unsafe as described in N.J.A.C. 5:23; and for applications for building permits to improve buildings and structures, including alterations, movement, repair, additions, rehabilitations, renovations, ordinary maintenance and minor work, substantial improvements, repairs of substantial damage, and any other improvement of or work on such buildings and structures, the Floodplain Administrator, in coordination with the Construction Official, shall:

- (1) Estimate the market value or require the applicant to obtain a professional appraisal prepared by a qualified independent appraiser, of the market value of the building or structure before the start of construction of the proposed work; in the case of repair, the market value of the building or structure shall be the market value before the damage occurred and before any repairs are made.
- (2) Determine and include the costs of all ordinary maintenance and minor work, as discussed in Section 94-2.2, performed in the floodplain regulated by this ordinance in addition to the costs of those improvements regulated by the Construction Official in substantial damage and substantial improvement calculations.
- (3) Compare the cost to perform the improvement, the cost to repair the damaged building to its pre-damaged condition, or the combined costs of improvements and repairs, where applicable, to the market value of the building or structure.
- (4) Determine and document whether the proposed work constitutes substantial improvement or repair of substantial damage.

- (5) Notify the applicant in writing when it is determined that the work constitutes substantial improvement or repair of substantial damage and that compliance with the flood resistant construction requirements of the building code is required and notify the applicant in writing when it is determined that work does not constitute substantial improvement or repair of substantial damage. The Floodplain Administrator shall also provide all letters documenting substantial damage and compliance with flood resistant construction requirements of the building code to the NJDEP Bureau of Flood Engineering.

**94-3.15 Department records.** In addition to the requirements of the building code and these regulations, and regardless of any limitation on the period required for retention of public records, the Floodplain Administrator shall maintain and permanently keep and make available for public inspection all records that are necessary for the administration of these regulations and the flood provisions of the Uniform Construction Code, including Flood Insurance Studies, Flood Insurance Rate Maps; documents from FEMA that amend or revise FIRMs; NJDEP delineations, records of issuance of permits and denial of permits; records of ordinary maintenance and minor work, determinations of whether proposed work constitutes substantial improvement or repair of substantial damage; required certifications and documentation specified by the Uniform Construction Code and these regulations including as-built Elevation Certificates; notifications to adjacent communities, FEMA, and the State related to alterations of watercourses; assurance that the flood carrying capacity of altered waterways will be maintained; documentation related to variances, including justification for issuance or denial; and records of enforcement actions taken pursuant to these regulations and the flood resistant provisions of the Uniform Construction Code. The Floodplain Administrator shall also record the required elevation, determination method, and base flood elevation source used to determine the Local Design Flood Elevation in the floodplain development permit.

**94-3.16 Liability.** The Floodplain Administrator and any employee charged with the enforcement of these regulations, while acting for the jurisdiction in good faith and without malice in the discharge of the duties required by these regulations or other pertinent law or ordinance, shall not thereby be rendered liable personally and is hereby relieved from personal liability for any damage accruing to persons or property as a result of any act or by reason of an act or omission in the discharge of official duties. Any suit instituted against an officer or employee because of an act performed by that officer or employee in the lawful discharge of duties and under the provisions of these regulations shall be defended by legal representative of the jurisdiction until the final termination of the proceedings. The Floodplain Administrator and any subordinate shall not be liable for cost in any action, suit or proceeding that is instituted in pursuance of the provisions of these regulations.

## **SECTION 94-4 PERMITS**

**94-4.1 Permits Required.** Any person, owner or authorized agent who intends to conduct any development in a flood hazard area shall first make application to the Floodplain Administrator and shall obtain the required permit. Depending on the nature and extent of proposed development that includes a building or structure, the Floodplain Administrator may determine that a floodplain development permit or approval is required in

addition to a building permit.

**94-4.2 Application for permit.** The applicant shall file an application in writing on a form furnished by the Floodplain Administrator. Such application shall:

- (1) Identify and describe the development to be covered by the permit.
- (2) Describe the land on which the proposed development is to be conducted by legal description, street address or similar description that will readily identify and definitively locate the site.
- (3) Indicate the use and occupancy for which the proposed development is intended.
- (4) Be accompanied by a site plan and construction documents as specified in Section 94-5 of these regulations, grading and filling plans and other information deemed appropriate by the Floodplain Administrator.
- (5) State the valuation of the proposed work, including the valuation of ordinary maintenance and minor work.
- (6) Be signed by the applicant or the applicant's authorized agent.
- (7) Include any recorded deeds required by this Chapter.

**94-4.3 Validity of permit.** The issuance of a permit under these regulations or the Uniform Construction Code shall not be construed to be a permit for, or approval of, any violation of this appendix or any other ordinance of the jurisdiction. The issuance of a permit based on submitted documents and information shall not prevent the Floodplain Administrator from requiring the correction of errors. The Floodplain Administrator is authorized to prevent occupancy or use of a structure or site which is in violation of these regulations or other ordinances of this jurisdiction.

**94-4.4 Expiration.** A permit shall become invalid when the proposed development is not commenced within 180 days after its issuance, or when the work authorized is suspended or abandoned for a period of 180 days after the work commences. Extensions shall be requested in writing and justifiable cause demonstrated. The Floodplain Administrator is authorized to grant, in writing, one or more extensions of time, for periods not more than 180 days each.

**94-4.5 Suspension or revocation.** The Floodplain Administrator is authorized to suspend or revoke a permit issued under these regulations wherever the permit is issued in error or on the basis of incorrect, inaccurate or incomplete information, or in violation of any ordinance or code of this jurisdiction.

**94-4.6 Certificates of occupancy.** Prior to the issuance of a certificate of occupancy for new construction or for a certificate of occupancy upon resale or a certificate of occupancy issued for any other purpose, an application for such certificate shall be submitted to the Building Department on the form provided by the Building Department, which application shall be accompanied by a recorded deed, recorded in

the Ocean County Clerk's Office at Toms River, New Jersey, which recorded deed shall contain the following specific language:

There is hereby imposed upon the lands described in this Deed a restrictive covenant advising all future owners of the said lands whether acquired by conveyance, inheritance or otherwise that the lands may only be used in accordance with flood regulations established by the Federal Emergency Management Agency (FEMA) in 44 CFR Parts 59 & 60, the Flood Hazard Area Control Act [N.J.A.C. 7:13] the Uniform Construction Code [N.J.A.C. 5:23] and this ordinance with the most restrictive requirements taking precedence if in conflict. A violation of any of these regulations may result in:

- A. An issuance of a summons returnable in the Municipal Court of the Township of Long Beach, or any other appropriate Court having jurisdiction, providing for a fine of not less than \$100 nor more than \$1,000 per day, or such greater or lesser fines as may be permitted by law for each and every day that any violation of the said Federal Emergency Management Agency flood protection regulations are violated; or
- B. Subject the owner of the lands to an action in the Chancery Division, Superior Court of New Jersey or any other court having injunctive jurisdiction for a mandatory injunction compelling the owner to remove any violations of the said Federal Emergency Management Agency regulations.

By acceptance of title to the lands encumbered hereby, any owner thereof whether title be acquired by Deed of conveyance, inheritance or otherwise, grants to the appropriate inspection officers of the Township of Long Beach the right upon 48 hours advance notice to inspect the areas of any structure located on the lands which area lies below the local design flood elevation (LDFE) as defined by this ordinance in order to determine compliance with such regulations and for a failure to permit such inspection, the owner of the lands may be subject to Complaint returnable in the Municipal Court of the Township of Long Beach and may be subject to a fine of not less than \$100 per day nor more than \$1,000 per day, or any such greater or lesser amounts as may be permitted by law for each and every day which inspection is refused.

## **SECTION 94-5 SITE PLANS AND CONSTRUCTION DOCUMENTS**

**94-5.1 Information for development in flood hazard areas.** The site plan or construction documents for any development subject to the requirements of these regulations shall be drawn to scale and shall include, as applicable to the proposed development:

- (1) Delineation of flood hazard areas, floodway boundaries and flood zone(s), base flood elevation(s), and ground elevations when necessary for review of the proposed development. For buildings that are located in more than one flood hazard area, the elevation and provisions associated with the most restrictive flood hazard area shall apply.
- (2) Where base flood elevations or floodway data are not included on the FIRM or in the Flood Insurance Study, they shall be established in accordance with Section 94-5.2.
- (3) Where the parcel on which the proposed development will take place will have more than 50 lots or is larger than 5 acres and base flood elevations are not included on the FIRM or in the Flood Insurance Study,

such elevations shall be established in accordance with Section 94-5.2(3) of these regulations.

- (4) Location of the proposed activity and proposed structures, and locations of existing buildings and structures; in coastal high hazard areas and Coastal A zones, new buildings shall be located landward of the reach of mean high tide.
- (5) Location, extent, amount, and proposed final grades of any filling, grading, or excavation.
- (6) Where the placement of fill is proposed, the amount, type, and source of fill material; compaction specifications; a description of the intended purpose of the fill areas; and evidence that the proposed fill areas are the minimum necessary to achieve the intended purpose.
- (7) Extent of any proposed alteration of sand dunes.
- (8) Existing and proposed alignment of any proposed alteration of a watercourse.
- (9) Floodproofing certifications, V Zone and Breakaway Wall Certifications, Operations and Maintenance Plans, Warning and Evacuation Plans and other documentation required pursuant to FEMA publications.

The Floodplain Administrator is authorized to waive the submission of site plans, construction documents, and other data that are required by these regulations but that are not required to be prepared by a registered design professional when it is found that the nature of the proposed development is such that the review of such submissions is not necessary to ascertain compliance.

**94-5.2 Information in flood hazard areas without base flood elevations**

**(approximate Zone A).** Where flood hazard areas are delineated on the effective or preliminary FIRM and base flood elevation data have not been provided, the applicant shall consult with the Floodplain Administrator to determine whether to:

- (1) Use the Approximation Method (Method 5) described in N.J.A.C. 7:13 in conjunction with Appendix 1 of the FHACA to determine the required flood elevation.
- (2) Obtain, review, and reasonably utilize data available from a Federal, State or other source when those data are deemed acceptable to the Floodplain Administrator to reasonably reflect flooding conditions.
- (3) Determine the base flood elevation in accordance with accepted hydrologic and hydraulic engineering techniques according to Method 6 as described in N.J.A.C. 7:13. Such analyses shall be performed and sealed by a licensed professional engineer.

Studies, analyses, and computations shall be submitted in sufficient detail to allow review and approval by the Floodplain Administrator prior to floodplain development permit issuance. The accuracy of data submitted for such determination shall be the



responsibility of the applicant. Where the data are to be used to support a Letter of Map Change (LOMC) from FEMA, the applicant shall be responsible for satisfying the submittal requirements and pay the processing fees.

**94-5.3 Analyses and certifications by a Licensed Professional Engineer.** As applicable to the location and nature of the proposed development activity, and in addition to the requirements of this section, the applicant shall have the following analyses signed and sealed by a licensed professional engineer for submission with the site plan and construction documents:

- (1) For development activities proposed to be located in a regulatory floodway, a floodway encroachment analysis that demonstrates that the encroachment of the proposed development will not cause any increase in base flood elevations; where the applicant proposes to undertake development activities that do increase base flood elevations, the applicant shall submit such analysis to FEMA as specified in Section 94-5.4 of these regulations and shall submit the Conditional Letter of Map Revision, if issued by FEMA, with the site plan and construction documents.
- (2) For development activities proposed to be located in a riverine flood hazard area where base flood elevations are included in the FIS or FIRM but floodways have not been designated, hydrologic and hydraulic analyses that demonstrate that the cumulative effect of the proposed development, when combined with all other existing and anticipated flood hazard area encroachments will not increase the base flood elevation more than 0.2 feet at any point within the jurisdiction. This requirement does not apply in isolated flood hazard areas not connected to a riverine flood hazard area or in flood hazard areas identified as Zone AO or Zone AH.
- (3) For alteration of a watercourse, an engineering analysis prepared in accordance with standard engineering practices which demonstrates that the flood-carrying capacity of the altered or relocated portion of the watercourse will not be decreased, and certification that the altered watercourse shall be maintained, neither increasing nor decreasing the channel's flood-carrying capacity. The applicant shall submit the analysis to FEMA as specified in Section 94-5.4 of these regulations. The applicant shall notify the chief executive officer of all affected adjacent jurisdictions, the NJDEP's Bureau of Flood Engineering and the Division of Land Resource Protection; and shall provide documentation of such notifications.
- (4) For activities that propose to alter sand dunes in coastal high hazard areas (Zone V) and Coastal A Zones, an engineering analysis that demonstrates that the proposed alteration will not increase the potential for flood damage and documentation of the issuance of a New Jersey Coastal Zone Management permit under N.J.A.C. 7:7.
- (5) For analyses performed using Methods 5 and 6 (as described in N.J.A.C. 7:13) in flood hazard zones without base flood elevations (approximate A zones).

**94-5.4 Submission of additional data.** When additional hydrologic, hydraulic or other engineering data, studies, and additional analyses are submitted to support an application, the applicant has the right to seek a Letter of Map Change (LOMC) from FEMA to change the base flood elevations, change floodway boundaries, or change boundaries of flood hazard areas shown on FIRMs, and to submit such data to FEMA for such purposes. The analyses shall be prepared by a licensed professional engineer in a format required by FEMA. Submittal requirements and processing fees shall be the responsibility of the applicant.

## **SECTION 94-6 INSPECTIONS**

**94-6.1 General.** Development for which a permit is required shall be subject to inspection. Approval as a result of an inspection shall not be construed to be an approval of a violation of the provisions of these regulations or the building code. Inspections presuming to give authority to violate or cancel the provisions of these regulations or the building code or other ordinances shall not be valid.

**94-6.2 Inspections of development.** The Floodplain Administrator shall inspect all development in flood hazard areas authorized by issuance of permits under these regulations. The Floodplain Administrator shall inspect flood hazard areas from time to time to determine if development is undertaken without issuance of a permit.

**94-6.3 Buildings and structures.** The Construction Official shall make or cause to be made, inspections for buildings and structures in flood hazard areas authorized by permit in accordance with the Uniform Construction Code, N.J.A.C. 5:23.

- 1) **Lowest floor elevation.** Upon placement of the lowest floor, including the basement, and prior to further vertical construction, certification of the elevation required in Section 94-15.2 shall be submitted to the Construction Official on an Elevation Certificate.
- 2) **Lowest horizontal structural member.** In V zones and Coastal A zones, upon placement of the lowest floor, including the basement, and prior to further vertical construction, certification of the elevation required in Section 94-15.2 shall be submitted to the Construction Official on an Elevation Certificate.
- 3) **Installation of attendant utilities** (electrical, heating, ventilating, air-conditioning, and other service equipment) and sanitary facilities elevated as discussed in Section 94-15.2.
- 4) **Final inspection.** Prior to the final inspection, certification of the elevation required in Section 94-15.2 shall be submitted to the Construction Official on an Elevation Certificate.

**94-6.4 Manufactured homes.** The Floodplain Administrator shall inspect manufactured homes that are installed or replaced in flood hazard areas to determine compliance with the requirements of these regulations and the conditions of the issued

permit. Upon placement of a manufactured home, certification of the elevation of the lowest floor shall be submitted on an Elevation Certificate to the Floodplain Administrator prior to the final inspection.

## **SECTION 94-7 VARIANCES**

**94-7.1 General.** The Board of Commissioners shall hear and decide requests for variances. The Board of Commissioners shall base its determination on technical justifications submitted by applicants, the considerations for issuance in Section 94-7.5, the conditions of issuance set forth in Section 94-7.6, and the comments and recommendations of the Floodplain Administrator and, as applicable, the Construction Official. The Board of Commissioners has the right to attach such conditions to variances as it deems necessary to further the purposes and objectives of these regulations.

**94-7.2 Historic structures.** A variance to the substantial improvement requirements of this ordinance is authorized provided that the repair or rehabilitation of a historic structure is completed according to N.J.A.C. 5:23-6.33, Section 1612 of the International Building Code and R322 of the International Residential Code, the repair or rehabilitation will not preclude the structure's continued designation as a historic structure, the structure meets the definition of the historic structure as described by this ordinance, and the variance is the minimum necessary to preserve the historic character and design of the structure.

**94-7.3 Functionally dependent uses.** A variance is authorized to be issued for the construction or substantial improvement necessary for the conduct of a functionally dependent use provided the variance is the minimum necessary to allow the construction or substantial improvement, and that all due consideration has been given to use of methods and materials that minimize flood damage during the base flood and create no additional threats to public safety.

**94-7.4 Restrictions in floodways.** A variance shall not be issued for any proposed development in a floodway when any increase in flood levels would result during the base flood discharge, as evidenced by the applicable analysis and certification required in Section 94-5.3(1) of these regulations.

**94-7.5 Considerations.** In reviewing requests for variances, all technical evaluations, all relevant factors, all other portions of these regulations, and the following shall be considered:

- (1) The danger that materials and debris may be swept onto other lands resulting in further injury or damage.
- (2) The danger to life and property due to flooding or erosion damage.
- (3) The susceptibility of the proposed development, including contents, to flood damage and the effect of such damage on current and future owners.
- (4) The importance of the services provided by the proposed development to the community.

- (5) The availability of alternate locations for the proposed development that are not subject to flooding or erosion and the necessity of a waterfront location, where applicable.
- (6) The compatibility of the proposed development with existing and anticipated development.
- (7) The relationship of the proposed development to the comprehensive plan and floodplain management program for that area.
- (8) The safety of access to the property in times of flood for ordinary and emergency vehicles.
- (9) The expected heights, velocity, duration, rate of rise and debris and sediment transport of the floodwater and the effects of wave action, where applicable, expected at the site.
- (10) The costs of providing governmental services during and after flood conditions including maintenance and repair of public utilities and facilities such as sewer, gas, electrical and water systems, streets, and bridges.

**94-7.6 Conditions for issuance.** Variances shall only be issued upon:

- (1) Submission by the applicant of a showing of good and sufficient cause that the unique characteristics of the size, configuration or topography of the site limit compliance with any provision of these regulations or renders the elevation standards of the building code inappropriate.
- (2) A determination that failure to grant the variance would result in exceptional hardship due to the physical characteristics of the land that render the lot undevelopable.
- (3) A determination that the granting of a variance will not result in increased flood heights, additional threats to public safety, extraordinary public expense, nor create nuisances, cause fraud on or victimization of the public or conflict with existing local laws or ordinances.
- (4) A determination that the variance is the minimum necessary, considering the flood hazard, to afford relief.
- (5) Notification to the applicant in writing over the signature of the Floodplain Administrator that the issuance of a variance to construct a structure below the base flood level will result in increased premium rates for flood insurance up to amounts as high as \$25 for \$100 of insurance coverage, and that such construction below the base flood level increases risks to life and property.

## **SECTION 94-8 VIOLATIONS**

**94-8.1 Violations.** Any development in any flood hazard area that is being

performed without an issued permit or that is in conflict with an issued permit shall be deemed a violation. A building or structure without the documentation of elevation of the lowest floor, the lowest horizontal structural member if in a V or Coastal A Zone, other required design certifications, or other evidence of compliance required by the building code is presumed to be a violation until such time as that documentation is provided.

**94-8.2 Authority.** The Floodplain Administrator is authorized to serve notices of violation or stop work orders to owners of property involved, to the owner's agent, or to the person or persons doing the work for development that is not within the scope of the Uniform Construction Code, but is regulated by these regulations and that is determined to be a violation.

**94-8.3 Unlawful continuance.** Any person who shall continue any work after having been served with a notice of violation or a stop work order, except such work as that person is directed to perform to remove or remedy a violation or unsafe condition, shall be subject to penalties as prescribed by N.J.S.A. 40:49-5 as appropriate.

**94-8.4 Review Period to Correct Violations.** A 30-day period shall be given to the property owner as an opportunity to cure or abate the condition. The property owner shall also be afforded an opportunity for a hearing before the court designated by the Township of Long Beach for an independent determination concerning the violation. Subsequent to the expiration of the 30-day period, a fine greater than \$1,250.00 may be imposed if a court has not determined otherwise or, upon reinspection of the property, it is determined that the abatement has not been substantially completed.

## SECTION 94-9 DEFINITIONS

**94-9.1 General.** The following words and terms shall, for the purposes of these regulations, have the meanings shown herein. Other terms are defined in the Uniform Construction Code N.J.A.C. 5:23 and terms are defined where used in the International Residential Code and International Building Code (rather than in the definitions section). Where terms are not defined, such terms shall have ordinarily accepted meanings such as the context implies.

### **94-9.2 Definitions**

#### **30 DAY PERIOD**

The period of time prescribed by N.J.S.A. 40:49-5 in which a property owner is afforded the opportunity to correct zoning and solid waste disposal after a notice of violation pertaining to this ordinance has been issued.

#### **100 YEAR FLOOD ELEVATION**

Elevation of flooding having a 1% annual chance of being equaled or exceeded in a given year which is also referred to as the Base Flood Elevation.

#### **500 YEAR FLOOD ELEVATION**

Elevation of flooding having a 0.2% annual chance of being equaled or exceeded in a

given year.

## A ZONES

Areas of 'Special Flood Hazard in which the elevation of the surface water resulting from a flood that has a 1% annual chance of equaling or exceeding the Base Flood Elevation (BFE) in any given year shown on the Flood Insurance Rate Map (FIRM) zones A, AE, AH, A1–A30, AR, AR/A, AR/AE, AR/A1– A30, AR/AH, and AR/AO. When used in reference to the development of a structure in this ordinance, A Zones are not inclusive of Coastal A Zones because of the higher building code requirements for Coastal A Zones.

## AH ZONES

Areas subject to inundation by 1-percent-annual-chance shallow flooding (usually areas of ponding) where average depths are between one and three feet. Base Flood Elevations (BFEs) derived from detailed hydraulic analyses are shown in this zone.

## AO ZONES

Areas subject to inundation by 1-percent-annual-chance shallow flooding (usually sheet flow on sloping terrain) where average depths are between one and three feet.

## ACCESSORY STRUCTURE

Accessory structures are also referred to as appurtenant structures. An accessory structure is a structure which is on the same parcel of property as a principal structure and the use of which is incidental to the use of the principal structure. For example, a residential structure may have a detached garage or storage shed for garden tools as accessory structures. Other examples of accessory structures include gazebos, picnic pavilions, boathouses, small pole barns, storage sheds, and similar buildings.

## AGRICULTURAL STRUCTURE

A structure used solely for agricultural purposes in which the use is exclusively in connection with the production, harvesting, storage, drying, or raising of agricultural commodities, including the raising of livestock. Communities must require that new construction or substantial improvements of agricultural structures be elevated or floodproofed to or above the Base Flood Elevation (BFE) as any other nonresidential building. Under some circumstances it may be appropriate to wet-floodproof certain types of agricultural structures when located in wide, expansive floodplains through issuance of a variance. This should only be done for structures used for temporary storage of equipment or crops or temporary shelter for livestock and only in circumstances where it can be demonstrated that agricultural structures can be designed in such a manner that results in minimal damage to the structure and its contents and will create no additional threats to public safety. New construction or substantial improvement of livestock confinement buildings, poultry houses, dairy operations, similar livestock operations and any structure that represents more than a minimal investment must meet the elevation or dry-floodproofing requirements of 44 CFR 60.3(c)(3).

## AREA OF SHALLOW FLOODING

A designated Zone AO, AH, AR/AO or AR/AH (or VO) on a community's Flood Insurance Rate Map (FIRM) with a one percent or greater annual chance of flooding to an average depth of one to three feet where a clearly defined channel does not exist, where the path of flooding is unpredictable, and where velocity flow may be evident. Such flooding is characterized by ponding or sheet flow. AREA OF SPECIAL FLOOD HAZARD – see SPECIAL FLOOD HAZARD AREA

#### ALTERATION OF A WATERCOURSE

A dam, impoundment, channel relocation, change in channel alignment, channelization, or change in cross-sectional area of the channel or the channel capacity, or any other form of modification which may alter, impede, retard or change the direction and/or velocity of the riverine flow of water during conditions of the base flood.

#### ASCE 7

The standard for the Minimum Design Loads for Buildings and Other Structures, referenced by the building code and developed and published by the American Society of Civil Engineers, Reston, VA. which includes but is not limited to methodology and equations necessary for determining structural and flood-related design requirements and determining the design requirements for structures that may experience a combination of loads including those from natural hazards. Flood related equations include those for determining erosion, scour, lateral, vertical, hydrostatic, hydrodynamic, buoyancy, breaking wave, and debris impact.

#### ASCE 24

The standard for Flood Resistant Design and Construction, referenced by the building code and developed and published by the American Society of Civil Engineers, Reston, VA. References to ASCE 24 shall mean ASCE 24-14 or the most recent version of ASCE 24 adopted in the UCC Code [N.J.A.C. 5:23].

#### BASE FLOOD ELEVATION (BFE)

The water surface elevation resulting from a flood that has a 1-percent or greater chance of being equaled or exceeded in any given year, as shown on a published Flood Insurance Study (FIS), or preliminary flood elevation guidance from FEMA. May also be referred to as the "100-year flood elevation".

#### BASEMENT

Any area of the building having its floor subgrade (below ground level) on all sides.

#### BEST AVAILABLE FLOOD HAZARD DATA

The most recent available preliminary flood risk guidance FEMA has provided. The Best Available Flood Hazard Data may be depicted on but not limited to Advisory Flood Hazard Area Maps, Work Maps, or Preliminary FIS and FIRM.

#### BEST AVAILABLE FLOOD HAZARD DATA AREA

The areal mapped extent associated with the most recent available preliminary flood risk guidance FEMA has provided. The Best Available Flood Hazard Data may be depicted on but not limited to Advisory Flood Hazard Area Maps, Work Maps, or Preliminary FIS and FIRM.

#### BEST AVAILABLE FLOOD HAZARD DATA ELEVATION

The most recent available preliminary flood elevation guidance FEMA has provided. The Best Available Flood Hazard Data may be depicted on but not limited to Advisory Flood Hazard Area Maps, Work Maps, or Preliminary FIS and FIRM.

#### BREAKAWAY WALLS

Any type of wall subject to flooding that is not required to provide structural support to a building or other structure and that is designed and constructed such that, below the Local Design Flood Elevation, it will collapse under specific lateral loads such that (1) it allows the free passage of floodwaters, and (2) it does not damage the structure or supporting foundation system. Certification in the V Zone Certificate of the design, plans, and specifications by a licensed design professional that these walls are in accordance with accepted standards of practice is required as part of the permit application for new and substantially improved V Zone and Coastal A Zone structures. A completed certification must be submitted at permit application.

#### BUILDING

Per the FHACA, "Building" means a structure enclosed with exterior walls or fire walls, erected and framed of component structural parts, designed for the housing, shelter, enclosure, and support of individuals, animals, or property of any kind. A building may have a temporary or permanent foundation. A building that is intended for regular human occupation and/or residence is considered a habitable building.

#### COASTAL A ZONE

An Area of Special Flood Hazard starting from a Velocity (V) Zone and extending up to the landward Limit of the Moderate Wave Action delineation. Where no V Zone is mapped the Coastal A Zone is the portion between the open coast and the landward Limit of the Moderate Wave Action delineation. Coastal A Zones may be subject to wave effects, velocity flows, erosion, scour, or a combination of these forces. Construction and development in Coastal A Zones is to be regulated similarly to V Zones/Coastal High Hazard Areas except as allowed by ASCE 24.

#### COASTAL HIGH HAZARD AREA

An Area of Special Flood Hazard inclusive of the V Zone extending from offshore to the inland limit of a primary frontal dune along an open coast and any other area subject to high velocity wave action from storms or seismic sources.

#### CONDITIONAL LETTER OF MAP REVISION

A Conditional Letter of Map Revision (CLOMR) is FEMA's comment on a proposed project that would, upon construction, affect the hydrologic or hydraulic characteristics of a



flooding source and thus result in the modification of the existing regulatory floodway, the effective Base Flood Elevations (BFEs), or the Special Flood Hazard Area (SFHA). The letter does not revise an effective NFIP map, it indicates whether the project, if built as proposed, would be recognized by FEMA. FEMA charges a fee for processing a CLOMR to recover the costs associated with the review that is described in the Letter of Map Change (LOMC) process. Building permits cannot be issued based on a CLOMR, because a CLOMR does not change the NFIP map.

#### CONDITIONAL LETTER OF MAP REVISION - FILL –

A Conditional Letter of Map Revision - Fill (CLOMR-F) is FEMA's comment on a proposed project involving the placement of fill outside of the regulatory floodway that would, upon construction, affect the hydrologic or hydraulic characteristics of a flooding source and thus result in the modification of the existing regulatory floodway, the effective Base Flood Elevations (BFEs), or the Special Flood Hazard Area (SFHA). The letter does not revise an effective NFIP map, it indicates whether the project, if built as proposed, would be recognized by FEMA. FEMA charges a fee for processing a CLOMR to recover the costs associated with the review that is described in the Letter of Map Change (LOMC) process. Building permits cannot be issued based on a CLOMR, because a CLOMR does not change the NFIP map.

#### CRITICAL BUILDING

Per the FHACA, “Critical Building” means that:

- a. It is essential to maintaining continuity of vital government operations and/or supporting emergency response, sheltering, and medical care functions before, during, and after a flood, such as a hospital, medical clinic, police station, fire station, emergency response center, or public shelter; or
- b. It serves large numbers of people who may be unable to leave the facility through their own efforts, thereby hindering or preventing safe evacuation of the building during a flood event, such as a school, college, dormitory, jail or detention facility, day care center, assisted living facility, or nursing home.

#### DEEP FOUNDATIONS

Per ASCE 24, deep foundations refer to those foundations constructed on erodible soils in Coastal High Hazard and Coastal A Zones which are founded on piles, drilled shafts, caissons, or other types of deep foundations and are designed to resist erosion and scour and support lateral and vertical loads as described in ASCE 7. Foundations shall extend to 10 feet below Mean Water Level (MWL) unless the design demonstrates that pile penetration will provide sufficient depth and stability as determined by ASCE 24, ASCE 7, and additional geotechnical investigations if any unexpected conditions are encountered during construction.

#### DEVELOPMENT

Any manmade change to improved or unimproved real estate, including but not limited to,

buildings or other structures, tanks, temporary structures, temporary or permanent storage of materials, mining, dredging, filling, grading, paving, excavations, drilling operations and other land-disturbing activities.

#### DRY FLOODPROOFING

A combination of measures that results in a non-residential structure, including the attendant utilities and equipment as described in the latest version of ASCE 24, being watertight with all elements substantially impermeable and with structural components having the capacity to resist flood loads.

#### ELEVATED BUILDING

A building that has no basement and that has its lowest elevated floor raised above ground level by foundation walls, shear walls, posts, piers, pilings, or columns. Solid perimeter foundations walls are not an acceptable means of elevating buildings in V and VE Zones.

#### ELEVATION CERTIFICATE

An administrative tool of the National Flood Insurance Program (NFIP) that can be used to provide elevation information, to determine the proper insurance premium rate, and to support an application for a Letter of Map Amendment (LOMA) or Letter of Map Revision based on fill (LOMR-F).

#### ENCROACHMENT

The placement of fill, excavation, buildings, permanent structures or other development into a flood hazard area which may impede or alter the flow capacity of riverine flood hazard areas.

#### FEMA PUBLICATIONS

Any publication authored or referenced by FEMA related to building science, building safety, or floodplain management related to the National Flood Insurance Program. Publications shall include but are not limited to technical bulletins, desk references, and American Society of Civil Engineers Standards documents including ASCE 24.

#### FLOOD OR FLOODING

- a. A general and temporary condition of partial or complete inundation of normally dry land areas from:
  1. The overflow of inland or tidal waters.
  2. The unusual and rapid accumulation or runoff of surface waters from any source.
  3. Mudslides (i.e. mudflows) which are proximately caused by flooding as defined in (a) (2) of this definition and are akin to a river or liquid and flowing mud on the surfaces of normally dry land areas, as when earth is carried by a current of water and deposited along the path of the current.

- b. The collapse or subsidence of land along the shore of a lake or other body of water as a result of erosion or undermining caused by waves or currents of water exceeding anticipated cyclical levels or suddenly caused by an unusually high water level in a natural body of water, accompanied by a severe storm, or by an unanticipated force of nature, such as flash flood or an abnormal tidal surge, or by some similarly unusual and unforeseeable event which results in flooding as defined in paragraph (a)(1) of this definition.

#### FLOOD HAZARD AREA DESIGN FLOOD ELEVATION

Per the FHACA, the peak water surface elevation that will occur in a water during the flood hazard area design flood. This elevation is determined via available flood mapping adopted by the State, flood mapping published by FEMA (including effective flood mapping dated on or after January 31, 1980, or any more recent advisory, preliminary, or pending flood mapping; whichever results in higher flood elevations, wider floodway limits, greater flow rates, or indicates a change from an A zone to a V zone or coastal A zone), approximation, or calculation pursuant to the Flood Hazard Area Control Act Rules at N.J.A.C. 7:13-3.1 – 3.6 and is typically higher than FEMA's base flood elevation. A water that has a drainage area measuring less than 50 acres does not possess, and is not assigned, a flood hazard area design flood elevation.

#### FLOOD HAZARD PROTECTION AREA (FHPA)

An area requiring higher construction standards because of the erodibility of the underlying soil characteristics and the vulnerability of structures in these areas to erosion and scour if dunes and/or flood protection infrastructure seaward of these areas are breached. These areas are established pursuant to ASCE 24-14 1.3.2 and the commentary discussed in these standards in C4.1.1, an analysis of underlying soil characteristics, and an evaluation of existing natural and man-made flood protection infrastructure. A predicted sea level rise will adversely affect construction in areas subject to erosion as storm surges and wave velocities affect more structures further inland from the current shoreline. The increased foundation costs for constructing to higher standards in these areas will be offset by lower flood damages and mitigation costs over the expected life of the structure. These areas are legally established through the Flood Damage Prevention Ordinance adoption process and described in the ordinance. These areas will also be established as part of the master plan for consideration by the Planning Board and/or the Zoning Board of Adjustment prior to either board's approval of new development projects.

#### FLOOD INSURANCE RATE MAP (FIRM)

The official map on which the Federal Emergency Management Agency has delineated both the areas of special flood hazards and the risk premium zones applicable to the community.

#### FLOOD INSURANCE STUDY (FIS)

The official report in which the Federal Emergency Management Agency has provided flood profiles, as well as the Flood Insurance Rate Map(s) and the water surface elevation of the base flood.

#### FLOODPLAIN OR FLOOD PRONE AREA

Any land area susceptible to being inundated by water from any source. See "Flood or flooding."

## FLOODPLAIN MANAGEMENT REGULATIONS

Zoning ordinances, subdivision regulations, building codes, health regulations, special purpose ordinances (such as a floodplain ordinance, grading ordinance, and erosion control ordinance) and other applications of police power. The term describes such State or local regulations, in any combination thereof, which provide standards for the purpose of flood damage prevention and reduction.

## FLOODPROOFING

Any combination of structural and nonstructural additions, changes, or adjustments to structures which reduce or eliminate flood damage to real estate or improved real property, water and sanitary facilities, structures, and their contents.

## FLOODPROOFING CERTIFICATE

Certification by a licensed design professional that the design and methods of construction for floodproofing a non-residential structure are in accordance with accepted standards of practice to a proposed height above the structure's lowest adjacent grade that meets or exceeds the Local Design Flood Elevation. A completed floodproofing certificate is required at permit application.

## FLOODWAY

The channel of a river or other watercourse and the adjacent land areas that must be reserved in order to discharge the base flood without cumulatively increasing the water surface elevation more than 0.2 foot.

## FREEBOARD

A factor of safety usually expressed in feet above a flood level for purposes of floodplain management. "Freeboard" tends to compensate for the many unknown factors that could contribute to flood heights greater than the height calculated for a selected size flood and floodway conditions, such as wave action, bridge openings, and the hydrological effect of urbanization of the watershed.

## FUNCTIONALLY DEPENDENT USE

A use that cannot perform its intended purpose unless it is located or carried out in close proximity to water, including only docking facilities, port facilities necessary for the loading or unloading of cargo or passengers, and shipbuilding and ship repair facilities. The term does not include long-term storage or related manufacturing facilities.

## HABITABLE BUILDING

Pursuant to the FHACA Rules (N.J.A.C. 7:13), means a building that is intended for regular human occupation and/or residence. Examples of a habitable building include a

single-family home, duplex, multi-residence building, or critical building; a commercial building such as a retail store, restaurant, office building, or gymnasium; an accessory structure that is regularly occupied, such as a garage, barn, or workshop; mobile and manufactured homes, and trailers intended for human residence, which are set on a foundation and/or connected to utilities, such as in a mobile home park (not including campers and recreational vehicles); and any other building that is regularly occupied, such as a house of worship, community center, or meeting hall, or animal shelter that includes regular human access and occupation. Examples of a non-habitable building include a bus stop shelter, utility building, storage shed, self-storage unit, construction trailer, or an individual shelter for animals such as a doghouse or outdoor kennel.

#### HARDSHIP

As related to Section 94-7 of this ordinance, meaning the exceptional hardship that would result from a failure to grant the requested variance. The Board of Commissioners requires that the variance be exceptional, unusual, and peculiar to the property involved. Mere economic or financial hardship alone is not exceptional. Inconvenience, aesthetic considerations, physical handicaps, personal preferences, or the disapproval of one's neighbors likewise cannot, as a rule, qualify as an exceptional hardship. All of these problems can be resolved through other means without granting a variance, even if the alternative is more expensive, or requires the property owner to build elsewhere or put the parcel to a different use than originally intended.

#### HIGHEST ADJACENT GRADE

The highest natural elevation of the ground surface prior to construction next to the proposed or existing walls of a structure.

#### HISTORIC STRUCTURE

Any structure that is:

- a. Listed individually in the National Register of Historic Places (a listing maintained by the Department of Interior) or preliminarily determined by the Secretary of the Interior as meeting the requirements for individual listing on the National Register;
- b. Certified or preliminarily determined by the Secretary of the Interior as contributing to the historical significance of a registered historic district or a district preliminarily determined by the Secretary to qualify as a registered historic district;
- c. Individually listed on a State inventory of historic places in States with historic preservation programs which have been approved by the Secretary of the Interior; or
- d. Individually listed on a local inventory of historic places in communities with historic preservation programs that have been certified either:
  1. By an approved State program as determined by the Secretary of the Interior; or
  2. Directly by the Secretary of the Interior in States without approved programs.

## LAWFULLY EXISTING

Per the FHACA, means an existing fill, structure and/or use, which meets all Federal, State, and local laws, and which is not in violation of the FHACA because it was established:

- a. Prior to January 31, 1980; or
- b. On or after January 31, 1980, in accordance with the requirements of the FHACA as it existed at the time the fill, structure and/or use was established.

Note: Substantially damaged properties and substantially improved properties that have not been elevated are not considered “lawfully existing” for the purposes of the NFIP. This definition is included in this ordinance to clarify the applicability of any more stringent statewide floodplain management standards required under the FHACA.

## LETTER OF MAP AMENDMENT

A Letter of Map Amendment (LOMA) is an official amendment, by letter, to an effective National Flood Insurance Program (NFIP) map that is requested through the Letter of Map Change (LOMC) process. A LOMA establishes a property's location in relation to the Special Flood Hazard Area (SFHA). LOMAs are usually issued because a property has been inadvertently mapped as being in the floodplain but is actually on natural high ground above the base flood elevation. Because a LOMA officially amends the effective NFIP map, it is a public record that the community must maintain. Any LOMA should be noted on the community's master flood map and filed by panel number in an accessible location.

## LETTER OF MAP CHANGE

The Letter of Map Change (LOMC) process is a service provided by FEMA for a fee that allows the public to request a change in flood zone designation in an Area of Special Flood Hazard on a Flood Insurance Rate Map (FIRM). Conditional Letters of Map Revision, Conditional Letters of Map Revision – Fill, Letters of Map Revision, Letters of Map Revision-Fill, and Letters of Map Amendment are requested through the Letter of Map Change (LOMC) process.

## LETTER OF MAP REVISION

A Letter of Map Revision (LOMR) is FEMA's modification to an effective Flood Insurance Rate Map (FIRM). Letter of Map Revisions are generally based on the implementation of physical measures that affect the hydrologic or hydraulic characteristics of a flooding source and thus result in the modification of the existing regulatory floodway, the effective Base Flood Elevations (BFEs), or the Special Flood Hazard Area (SFHA). The LOMR officially revises the Flood Insurance Rate Map (FIRM) and sometimes the Flood Insurance Study (FIS) report, and when appropriate, includes a description of the modifications. The LOMR is generally accompanied by an annotated copy of the affected portions of the FIRM or FIS report. Because a LOMR officially revises the effective NFIP map, it is a public record that the community must maintain. Any LOMR should be noted on the community's master flood map and filed by panel number in an accessible location.

## LETTER OF MAP REVISION – FILL

A Letter of Map Revision Based on Fill (LOMR-F) is FEMA's modification of the Special Flood Hazard Area (SFHA) shown on the Flood Insurance Rate Map (FIRM) based on the placement of fill outside the existing regulatory floodway may be initiated through the Letter of Map Change (LOMC) Process. Because a LOMR-F officially revises the effective Flood Insurance Rate Map (FIRM) map, it is a public record that the community must maintain. Any LOMR-F should be noted on the community's master flood map and filed by panel number in an accessible location.

#### LICENSED DESIGN PROFESSIONAL

Licensed design professional shall refer to either a New Jersey Licensed Professional Engineer, licensed by the New Jersey State Board of Professional Engineers and Land Surveyors or a New Jersey Licensed Architect, licensed by the New Jersey State Board of Architects.

#### LICENSED PROFESSIONAL ENGINEER

A licensed professional engineer shall refer to individuals licensed by the New Jersey State Board of Professional Engineers and Land Surveyors.

#### LIMIT OF MODERATE WAVE ACTION (LiMWA)

Inland limit of the area affected by waves greater than 1.5 feet during the Base Flood. Base Flood conditions between the VE Zone and the LiMWA will be similar to, but less severe than those in the VE Zone.

#### LOCAL DESIGN FLOOD ELEVATION (LDFE)

The elevation reflective of the most recent available preliminary flood elevation guidance FEMA has provided as depicted on but not limited to Advisory Flood Hazard Area Maps, Work Maps, or Preliminary FIS and FIRM which is also inclusive of freeboard specified by the New Jersey Flood Hazard Area Control Act and Uniform Construction Codes and any additional freeboard specified in a community's ordinance. In no circumstances shall a project's LDFE be lower than a permit-specified Flood Hazard Area Design Flood Elevation or a valid NJDEP Flood Hazard Area Verification Letter plus the freeboard as required in ASCE 24 and the effective FEMA Base Flood Elevation.

#### LOWEST ADJACENT GRADE

The lowest point of ground, patio, or sidewalk slab immediately next a structure, except in AO Zones where it is the natural grade elevation.

#### LOWEST FLOOR

In A Zones, the lowest floor is the top surface of the lowest floor of the lowest enclosed area (including basement). In V Zones and coastal A Zones, the bottom of the lowest horizontal structural member of a building is the lowest floor. An unfinished or flood resistant enclosure, usable solely for the parking of vehicles, building access or storage in an area other than a basement is not considered a building's lowest floor provided that such enclosure is not built so as to render the structure in violation of other applicable non-

elevation design requirements of these regulations.

#### LOWEST HORIZONTAL STRUCTURAL MEMBER

In an elevated building in a Coastal A or Coastal High Hazard Zone, the lowest beam, joist, or other horizontal member that supports the building is the lowest horizontal structural member. Grade beams installed to support vertical foundation members where they enter the ground are not considered lowest horizontal members.

#### MANUFACTURED HOME

A structure that is transportable in one or more sections, eight (8) feet or more in width and greater than four hundred (400) square feet, built on a permanent chassis, designed for use with or without a permanent foundation when attached to the required utilities, and constructed to the Federal Manufactured Home Construction and Safety Standards and rules and regulations promulgated by the U.S. Department of Housing and Urban Development. The term also includes mobile homes, park trailers, travel trailers and similar transportable structures that are placed on a site for 180 consecutive days or longer.

#### MANUFACTURED HOME PARK OR SUBDIVISION

A parcel (or contiguous parcels) of land divided into two or more manufactured home lots for rent or sale.

#### MARKET VALUE

The price at which a property will change hands between a willing buyer and a willing seller, neither party being under compulsion to buy or sell and both having reasonable knowledge of relevant facts. As used in these regulations, the term refers to the market value of buildings and structures, excluding the land and other improvements on the parcel. Market value shall be determined by one of the following methods (1) Actual Cash Value (replacement cost depreciated for age and quality of construction), (2) tax assessment value adjusted to approximate market value by a factor provided by the Property Appraiser, or (3) established by a qualified independent appraiser.

#### NEW CONSTRUCTION

Structures for which the start of construction commenced on or after the effective date of the first floodplain regulation adopted by a community; includes any subsequent improvements to such structures. New construction includes work determined to be a substantial improvement.

#### NON-RESIDENTIAL

Pursuant to ASCE 24, any building or structure or portion thereof that is not classified as residential.

#### ORDINARY MAINTENANCE AND MINOR WORK

This term refers to types of work excluded from construction permitting under N.J.A.C.



5:23 in the March 5, 2018 New Jersey Register. Some of these types of work must be considered in determinations of substantial improvement and substantial damage in regulated floodplains under 44 CFR 59.1. These types of work include but are not limited to replacements of roofing, siding, interior finishes, kitchen cabinets, plumbing fixtures and piping, HVAC and air conditioning equipment, exhaust fans, built in appliances, electrical wiring, etc. Improvements necessary to correct existing violations of State or local health, sanitation, or code enforcement officials which are the minimum necessary to assure safe living conditions and improvements of historic structures as discussed in 44 CFR 59.1 shall not be included in the determination of ordinary maintenance and minor work.

#### PRIMARY FRONTAL DUNE AREA

This term refers to a continuous or nearly continuous mounds or ridges of sand with relatively steep seaward and landward slopes immediately landward and adjacent to the beach and subject to erosion and overtopping from high tides and waves during major coastal storms and may include mapped AO zones and both shaded and unshaded X zones.

#### RECREATIONAL VEHICLE

A vehicle that is built on a single chassis, 400 square feet or less when measured at the largest horizontal projection, designed to be self-propelled or permanently towable by a light-duty truck, and designed primarily not for use as a permanent dwelling but as temporary living quarters for recreational, camping, travel or seasonal use. A recreational vehicle is ready for highway use if it is on its wheels or jacking system, is attached to the site only by quick disconnect type utilities and security devices and has no permanently attached additions.

#### RESIDENTIAL

Pursuant to the ASCE 24:

- a. Buildings and structures and portions thereof where people live or that are used for sleeping purposes on a transient or non-transient basis;
- b. Structures including but not limited to one- and two-family dwellings, townhouses, condominiums, multi-family dwellings, apartments, congregate residences, boarding houses, lodging houses, rooming houses, hotels, motels, apartment buildings, convents, monasteries, dormitories, fraternity houses, sorority houses, vacation time-share properties; and
- c. institutional facilities where people are cared for or live on a 24-hour basis in a supervised environment, including but not limited to board and care facilities, assisted living facilities, halfway houses, group homes, congregate care facilities, social rehabilitation facilities, alcohol and drug centers, convalescent facilities, hospitals, nursing homes, mental hospitals, detoxification facilities, prisons, jails, reformatories, detention centers, correctional centers, and prerelease centers.

#### SOLID WASTE DISPOSAL

"Solid Waste Disposal" shall mean the storage, treatment, utilization, processing or final disposition of solid waste as described in N.J.A.C. 7:26-1.6 or the storage of unsecured materials as described in N.J.A.C. 7:13-2.3 for a period of greater than 6 months as specified in N.J.A.C. 7:26 which have been discharged, deposited, injected, dumped, spilled, leaked, or placed into any land or water such that such solid waste may enter the environment or be emitted into the air or discharged into any waters, including groundwaters.

## SPECIAL FLOOD HAZARD AREA

The greater of the following: (1) Land in the floodplain within a community subject to a one percent or greater chance of flooding in any given year, shown on the FIRM as Zone V, VE, V1-3-, A, AO, A1-30, AE, A99, or AH; (2) Land and the space above that land, which lies below the peak water surface elevation of the flood hazard area design flood for a particular water, as determined using the methods set forth in the New Jersey Flood Hazard Area Control Act in N.J.A.C. 7:13; (3) Riparian Buffers as determined in the New Jersey Flood Hazard Area Control Act in N.J.A.C. 7:13. Also referred to as the AREA OF SPECIAL FLOOD HAZARD.

**START OF CONSTRUCTION – The Start of Construction is as follows:**

- a. **For other than new construction or substantial improvements, under the Coastal Barrier Resources Act (CBRA),** this is the date the building permit was issued, provided that the actual start of construction, repair, rehabilitation, addition, placement or other improvement was within 180 days of the permit date. The actual start means either the first placement of permanent construction of a building on site, such as the pouring of a slab or footing, the installation of piles, the construction of columns or any work beyond the stage of excavation; or the placement of a manufactured (mobile) home on a foundation. For a substantial improvement, actual start of construction means the first alteration of any wall, ceiling, floor, or other structural part of a building, whether or not that alteration affects the external dimensions of the building.
- b. For the purposes of determining whether proposed construction must meet new requirements when National Flood Insurance Program (NFIP) maps are issued or revised and Base Flood Elevation's (BFEs) increase or zones change, the Start of Construction includes substantial improvement, and means the date the building permit was issued, provided the actual start of construction, repair, reconstruction, rehabilitation, addition placement, or other improvement was within 180 days of the permit date. The actual start means either the first placement of permanent construction of a structure on a site, such as the pouring of slab or footings, the installation of piles, the construction of columns, or any work beyond the stage of excavation; or the placement of a manufactured home on a foundation.

Permanent construction does not include land preparation, such as clearing, grading, and filling, nor does it include the installation of streets and/or walkways; nor does it include excavation for a basement, footings, piers, or foundations or the erection of temporary forms; nor does it include the installation on the property of accessory buildings, such as garages or sheds not occupied as dwelling units or not part of the main structure. Such development must also be permitted and must meet new requirements when National Flood Insurance Program (NFIP) maps are issued or revised and Base Flood Elevation's (BFEs) increase or zones change.

For a substantial improvement, the actual start of construction means the first alteration of any wall, ceiling, floor, or other structural part of a building, whether or not that alteration affects the external dimensions of the building.

For determining if new construction and substantial improvements within the Coastal Barrier Resources System (CBRS) can obtain flood insurance, a different definition applies.

## STRUCTURE

A walled and roofed building, a manufactured home, or a gas or liquid storage tank that is principally above ground.

## SUBSTANTIAL DAMAGE

Damage of any origin sustained by a structure whereby the cost of restoring the structure to its before damaged condition would equal or exceed 50 percent (50%) of the market value of the structure before the damage occurred.

## SUBSTANTIAL IMPROVEMENT

Any combination of reconstruction, rehabilitation, addition, or other improvement including those considered ordinary maintenance and minor work of a structure taking place over the period of open permit, the cumulative cost of which equals or exceeds fifty (50) percent of the market value of the structure before the "start of construction" of the improvement. This term includes structures which have incurred "substantial damage," regardless of the actual repair work performed. The term does not, however, include either:

- a. Any project for improvement of a structure to correct existing violations of State or local health, sanitary or safety code specifications which have been identified by the local floodplain administrator and code enforcement officer and which are the minimum necessary to assure safe living conditions; or
- b. Any alteration of a "historic structure", provided that the alteration will not preclude the structure's continued designation as a "historic structure."

## UTILITY AND MISCELLANEOUS GROUP U BUILDINGS AND STRUCTURES

Buildings and structures of an accessory character and miscellaneous structures not classified in any special occupancy, as described in ASCE 24.

## V ZONE CERTIFICATE

A certificate that contains a certification signed by a licensed design professional certifying that the designs, plans, and specifications and the methods of construction in V Zones and Coastal A Zones are in accordance with accepted standards of practice. This certificate also includes an optional Breakaway Wall Design Certification for enclosures in these zones below the Best Available Flood Hazard Data Elevation. A completed certification is required at permit application.

## V ZONES

Areas of Special Flood Hazard in which the elevation of the surface water resulting from a flood that has a 1% annual chance of equaling or exceeding the Base Flood Elevation in any given year shown on the Flood Insurance Rate Map (FIRM) zones V1-V30 and VE and is referred to as the Coastal High Hazard Area.

## VARIANCE

A grant of relief from the requirements of this section which permits construction in a manner otherwise prohibited by this section where specific enforcement would result in unnecessary hardship.

## VIOLATION

A development that is not fully compliant with these regulations or the flood provisions of the building code. A structure or other development without the elevation certificate, other certifications, or other evidence of compliance required in this ordinance is presumed to be in violation until such time as that documentation is provided.

## WATER SURFACE ELEVATION

The height, in relation to the North American Vertical Datum (NAVD) of 1988, (or other datum, where specified) of floods of various magnitudes and frequencies in the flood plains of coastal or riverine areas.

## WATERCOURSE

A river, creek, stream, channel, or other topographic feature in, on, through, or over which water flows at least periodically.

## WET FLOODPROOFING

Floodproofing method that relies on the use of flood damage resistant materials and construction techniques in areas of a structure that are below the Local Design Flood Elevation by intentionally allowing them to flood. The application of wet floodproofing as a flood protection technique under the National Flood Insurance Program (NFIP) is limited to enclosures below elevated residential and non-residential structures and to accessory and agricultural structures that have been issued variances by the community.

## X ZONES

Area of flood hazard, depicted on FEMA FIRMA maps. If shaded, it is an area of moderate flood hazard, usually the area between the limits of the 1% annual chance or 100- year and the 0.2% annual chance 500-year flood level. If unshaded, it is an area of minimal flood hazard, usually depicted on FIRMs as above the 0.2% annual chance or 500-year flood level.

## **SECTION 94-10 SUBDIVISIONS AND OTHER DEVELOPMENTS**

**94-10.1 General.** Any subdivision proposal, including proposals for manufactured home parks and subdivisions, or other proposed new development in a flood hazard area shall be reviewed to assure that:

- (1) All such proposals are consistent with the need to minimize flood damage.
- (2) All public utilities and facilities, such as sewer, gas, electric and water systems are located and constructed to minimize or eliminate flood damage.
- (3) Adequate drainage is provided to reduce exposure to flood hazards; in Zones AH and AO, adequate drainage paths shall be provided to guide floodwater around and away from structures.

**94-10.2 Subdivision requirements.** Where any portion of proposed subdivisions, including manufactured home parks and subdivisions, lies within a flood hazard area, the following shall be required:

- (1) The flood hazard area, including floodways, coastal high hazard areas, and Coastal A Zones, and base flood elevations, as appropriate, shall be delineated on tentative subdivision plats.
- (2) Residential building lots shall be provided with adequate buildable area outside the floodway.
- (3) The design criteria for utilities and facilities set forth in these regulations and appropriate codes shall be met.

## **SECTION 94-11 SITE IMPROVEMENT**

**94-11.1 Encroachment in floodways.** Development, land disturbing activity, and encroachments in floodways shall not be authorized unless it has been demonstrated through hydrologic and hydraulic analyses required in accordance with Section 94-5.3(1) of these regulations, that the proposed encroachment will not result in any increase in the base flood level during occurrence of the base flood discharge. If Section 94-5.3(1) is satisfied, proposed elevation, addition, or reconstruction of a lawfully existing structure within a floodway shall also be in accordance with Section 94-15.2 of this ordinance and the floodway requirements of N.J.A.C. 7:13.

**94-11.2 Prohibited in floodways.** The following are prohibited activities:

- (1) The storage of unsecured materials is prohibited within a floodway pursuant to N.J.A.C. 7:13.
- (2) Fill and new structures are prohibited in floodways per N.J.A.C. 7:13.

**94-11.3 Coastal High Hazard Areas (V Zones) and Coastal A Zones.** In Coastal High Hazard Areas and Coastal A Zones:

- (1) New buildings shall only be authorized landward of the reach of mean high

tide.

- (2) The placement of manufactured homes shall be prohibited except in an existing manufactured home park or subdivision.
- (3) Basements or enclosures that are below grade on all sides are prohibited.
- (4) The use of fill for structural support of buildings is prohibited.

**94-11.4 Sewer facilities.** All new and replaced sanitary sewer facilities, private sewage treatment plants (including all pumping stations and collector systems) and on-site waste disposal systems shall be designed in accordance with the New Jersey septic system regulations contained in N.J.A.C. 14A and N.J.A.C. 7:9A, the UCC Plumbing Subcode (N.J.A.C. 5:23) and Chapter 7, ASCE 24, to minimize or eliminate infiltration of floodwater into the facilities and discharge from the facilities into flood waters, or impairment of the facilities and systems.

**94-11.5 Water facilities.** All new and replacement water facilities shall be designed in accordance with the New Jersey Safe Drinking Water Act (N.J.A.C. 7:10) and the provisions of Chapter 7 ASCE 24, to minimize or eliminate infiltration of floodwater into the systems.

**94-11.6 Storm drainage.** Storm drainage shall be designed to convey the flow of surface waters to minimize or eliminate damage to persons or property.

In any AO and AE Flood Zones listed on the municipality's FIRM map, all new construction and substantial improvement of any residential structure shall be required to install adequate drainage paths or equivalent around the structure to guide floodwaters away from the structure and to drain directly to the street upon which the lot is located and shall be sloped and graded to prevent such water from draining onto any adjacent properties.

**94-11.7 Streets and sidewalks.** Streets and sidewalks shall be designed to minimize potential for increasing or aggravating flood levels.

**94-11.8 Limitations on placement of fill.** Subject to the limitations of these regulations, fill shall be designed to be stable under conditions of flooding including rapid rise and rapid drawdown of floodwater, prolonged inundation, and protection against flood-related erosion and scour. In addition to these requirements, when intended to support buildings and structures (Zone A only), fill shall comply with the requirements of the UCC (N.J.A.C. 5:23). Proposed fill and encroachments in flood hazard areas shall comply with the flood storage displacement limitations of N.J.A.C. 7:13.

Except for fill used for landscaping or drainage purposes during minor grading under and around buildings, the placement of fill requires a flood damage prevention permit and is subject to sections 94-11.3 and 94-11.9. No permits will be issued for the use of structural fill in a Coastal High Hazard Zone. All permitted fill must comply with sections 94-3.5, 94-3.8, and 94-5.1(6) [Note: Flood storage displacement engineering certifications required by section 94-5.1(6) are not applicable in Long Beach Township and are not required to be submitted]. Increasing the grade in excess of 18 inches on all lots in the AE and AO flood

zones shall also require a soil erosion application and plan be submitted to the Long Beach Township Engineer for review and approval prior to the placement of any additional fill or a grade change on the lot.

**94-11.9 Limitations on sites in coastal high hazard areas (V Zones) and Coastal A Zones.**

In coastal high hazard areas and Coastal A Zones, alteration of sand dunes shall be permitted only when the engineering analysis required by Section 94-5.3(4) of these regulations demonstrates that the proposed alteration will not increase the potential for flood damage. Construction or restoration of dunes under or around elevated buildings and structures shall comply with Section 94-15.9(3) of these regulations and as permitted under the NJ Coastal Zone Management Rules (N.J.A.C. 7:7).

**94-11.10 Hazardous Materials.** The placement or storage of any containers holding hazardous substances in a flood hazard area is prohibited unless the provisions of N.J.A.C. 7:13 which cover the placement of hazardous substances and solid waste is met.

**94-11.11 Space below the lowest first elevated floor.**

(4) Prior to construction, plans for any breakaway wall must be submitted to the Floodplain Administrator for approval.

**SECTION 94-12 MANUFACTURED HOMES**

**94-12.1 General.** All manufactured homes installed in flood hazard areas shall be installed pursuant to the Nationally Preemptive Manufactured Home Construction and Safety Standards Program (24 CFR 3280).

**94-12.2 Placement.** The placement of manufactured homes shall be prohibited except in an existing manufactured home or mobile home park.

**94-12.3 Elevation.** All new, relocated, and replacement manufactured homes to be placed or substantially improved in a flood hazard area shall be elevated such that the bottom of the frame is elevated to or above the elevation specified in Section 94-15.2.

**94-12.4 Foundations.** All new, relocated, and replacement manufactured homes, including substantial improvement of existing manufactured homes, shall be placed on permanent, reinforced foundations that are designed in accordance with Section R322 of the Residential Code.

**94-12.5 Anchoring.** All new, relocated, and replacement manufactured homes to be placed or substantially improved in a flood hazard area shall be installed using methods and practices which minimize flood damage and shall be securely anchored to an adequately anchored foundation system to resist flotation, collapse and lateral movement. This requirement is in addition to applicable State and local anchoring requirements for resisting wind forces.

**94-12.6 Enclosures.** Fully enclosed areas below elevated manufactured homes shall comply with the requirements of Section 94-15.2.

**94-12.7 Protection of mechanical equipment and outside appliances.** Mechanical equipment and outside appliances shall be elevated to or above the elevation of the bottom of the frame required in Section 94-15.2 of these regulations.

**Exception.** Where such equipment and appliances are designed and installed to prevent water from entering or accumulating within their components and the systems are constructed to resist hydrostatic and hydrodynamic loads and stresses, including the effects of buoyancy, during the occurrence of flooding up to the elevation required by Section 94-15.2, the systems and equipment shall be permitted to be located below that elevation. Electrical wiring systems shall be permitted below the design flood elevation provided they conform to the provisions of NFPA 70 (National Electric Code).

### **SECTION 94-13 RECREATIONAL VEHICLES**

**94-13.1 Placement prohibited.** The placement of recreational vehicles shall not be authorized in coastal high hazard areas and in floodways.

**94-13.2 Temporary placement.** Recreational vehicles in flood hazard areas shall be fully licensed and ready for highway use and shall be placed on a site for less than 180 consecutive days.

**94-13.3 Permanent placement.** Recreational vehicles that are not fully licensed and ready for highway use, or that are to be placed on a site for more than 180 consecutive days, shall meet the requirements of Section 94-15.2 for habitable buildings.

### **SECTION 94-14 TANKS**

**94-14.1** Underground and above-ground tanks shall be designed, constructed, installed, and anchored in accordance with ASCE 24 and N.J.A.C. 7:13.

### **SECTION 94-15 OTHER DEVELOPMENT AND BUILDING WORK**

**94-15.1 General requirements for other development and building work.** All development and building work, including man-made changes to improved or unimproved real estate for which specific provisions are not specified in these regulations or the Uniform Construction Code (N.J.A.C. 5:23), shall:

- (1) Be located and constructed to minimize flood damage;
- (2) Meet the limitations of Section 94-5.3(1) of this ordinance when located in a regulated floodway;
- (3) Be anchored to prevent flotation, collapse or lateral movement resulting from hydrostatic and hydrodynamic loads, including the effects of buoyancy, during the conditions of flooding up to the Local Design Flood Elevation determined according to Section 94-2.3;



- (4) Be constructed of flood damage-resistant materials as described in ASCE 24 Chapter 5;
- (5) Have mechanical, plumbing, and electrical systems above the Local Design Flood Elevation determined according to Section 94-2.3 or meet the requirements of ASCE 24 Chapter 7 which requires that attendant utilities are located above the Local Design Flood Elevation unless the attendant utilities and equipment are:
  - i. Specifically allowed below the Local Design Flood Elevation; and
  - ii. Designed, constructed, and installed to prevent floodwaters, including any backflow through the system from entering or accumulating within the components.
- (6) Not exceed the flood storage displacement limitations in fluvial flood hazard areas in accordance with N.J.A.C. 7:13; and
- (7) Not exceed the impacts to frequency or depth of offsite flooding as required by N.J.A.C. 7:13 in floodways.

**94-15.2 Requirements for Habitable Buildings and Structures.**

- 1) Construction and Elevation in A Zones not including Coastal A Zones, Flood Hazard Protection Area – A, and Flood Hazard Protection Area -X.
  - a. No portion of a building is located within a V Zone.
  - b. No portion of a building is located within a Coastal A Zone, unless a licensed design professional certifies that the building's foundation is designed in accordance with ASCE 24, Chapter 4.
  - c. All new construction and substantial improvement of any habitable building (as defined in Section 94-9) located in flood hazard areas shall have the lowest floor, including basement, together with the attendant utilities (including all electrical, heating, ventilating, air-conditioning and other service equipment) and sanitary facilities, elevated to or above the Local Design Flood Elevation as determined in Section 94-2.3, be in conformance with ASCE Chapter 7, and be confirmed by an Elevation Certificate..
  - d. All new construction and substantial improvements of non-residential structures shall:
    - i. Have the lowest floor, including basement, together with the attendant utilities (including all electrical, heating, ventilating, air-conditioning and other service equipment) and sanitary facilities, elevated to or above the Local Design Flood Elevation as determined in Section 94-2.3, be in conformance with ASCE Chapter 7, and be confirmed by an Elevation

Certificate; or

- ii. Together with the attendant utility and sanitary facilities, be designed so that below the Local Design Flood Elevation, the structure:
  1. Meets the requirements of ASCE 24 Chapters 2 and 7; and
  2. Is constructed according to the design plans and specifications provided at permit application and signed by a licensed design professional, is certified by that individual in a Floodproofing Certificate, and is confirmed by an Elevation Certificate.
  
- e. Enclosures – Any alteration, repair, reconstruction or improvement to a structure started after the enactment of this chapter shall not enclose the space below the lowest floor unless breakaway walls, open wood latticework, or insect screening are provided for in this section. All new construction and substantial improvements with fully enclosed areas below the lowest floor shall be used solely for parking of vehicles, building access, or storage in an area other than a basement and which are subject to flooding. Enclosures shall:
  - i. For habitable structures, be situated at or above the adjoining exterior grade along at least one entire exterior wall, in order to provide positive drainage of the enclosed area in accordance with N.J.A.C. 7:13; enclosures (including crawlspaces and basements) which are below grade on all sides are prohibited;
  - ii. Be designed to automatically equalize hydrostatic flood forces on exterior walls by allowing for the entry and exit of floodwaters unless the structure is non-residential and the requirements of 94-15.2(1)(d)ii are met;
  - iii. Be constructed to meet the requirements of ASCE 24 Chapter 2;
  - iv. Have openings documented on an Elevation Certificate; and
  - v. Have documentation that a deed restriction has been obtained for the lot if the enclosure is greater than six feet in height. This deed restriction shall be recorded in the Office of the County Clerk or the Registrar of Deeds and Mortgages in which the building is located, shall conform to the requirements in N.J.A.C.7:13, and shall be recorded within 90 days of receiving a Flood Hazard Area Control Act permit or prior to the start of any site disturbance (including pre-construction earth movement, removal of vegetation and

structures, or construction of the project), whichever is sooner. Deed restrictions must explain and disclose that:

1. The enclosure is likely to be inundated by floodwaters which may result in damage and/or inconvenience.
2. The depth of flooding that the enclosure would experience to the Flood Hazard Area Design Flood Elevation;

The deed restriction prohibits habitation of the enclosure and explains that converting the enclosure into a habitable area may subject the property owner to enforcement;

f. Specifications for Breakaway Walls

Any proposed breakaway walls shall conform with this Chapter and be constructed according to structural designs, plans and specifications conforming with ASCE 24 Chapter 4, signed by a licensed design professional, and certified by that individual in a Breakaway Wall Certificate. Prior to construction, plans for breakaway walls must be submitted to the Code Enforcement Official for approval.

g. Specifications for Slab Construction

All slabs shall be a minimum of one foot above the crown of the road or easement upon which the structure being serviced by such slab is located. Any building or structure which had a concrete slab below the elevation as required by this chapter prior to October 29, 2012, may have the concrete slab replaced at the elevation at which it existed prior to October 29, 2012, provided that the construction is not considered a substantial improvement subject to elevation to the Local Design Flood Elevation.

2) Construction and Elevation in V Zones, Coastal A Zones, Flood Hazard Protection Area – Primary Frontal Dune, and Flood Hazard Protection Area - V.

Coastal high-hazard areas (V or VE Zones) and Coastal A Zones are located within the areas of special flood hazard established in § 94-4. These areas have special flood hazards associated with high-velocity waters from tidal surges and hurricane wave wash. Flood Hazard Protection Areas were also established in recognition of the challenges posed by erodible soils to foundations in these areas. Therefore, the following provisions shall apply:

- a. All new construction and substantial improvements shall be elevated on pilings and columns according to structural designs, plans and specifications conforming with ASCE 24 Chapter 4 which are signed by a licensed design professional and certified by that individual in a V Zone Certificate.
- b. All new construction and substantial improvement of any habitable building (as defined in Section 94-9) located in coastal high hazard areas shall have the lowest horizontal structural member, together with the attendant utilities (including all electrical, heating, ventilating, air-conditioning and other service equipment) and sanitary facilities, elevated on pilings or columns to the Local Design Flood Elevation as determined in Section 94-2.3, be in conformance with ASCE Chapter 7 and be confirmed by an Elevation Certificate.
- c. All new construction and substantial improvements of non-residential structures shall:
  - i. Have the lowest horizontal structural member, including basement, together with the attendant utilities (including all electrical, heating, ventilating, air-conditioning and other service equipment) and sanitary facilities, elevated to or above the Local Design Flood Elevation as determined in Section 94-2.3, be in conformance with ASCE 24 Chapter 7, and be confirmed by an Elevation Certificate; or
  - ii. Together with the attendant utility and sanitary facilities, be designed so that below the Local Design Flood Elevation, the structure:
    - 1. Meets the requirements of ASCE 24 Chapters 4 and 7; and
    - 2. Is constructed according to the design plans and specifications provided at permit application and signed by a licensed design professional, is certified by that individual in a Floodproofing Certificate, and is confirmed by an Elevation Certificate.
- d. Space below the Primary/Lowest Floor - All new construction and substantial improvements shall have the space below the lowest floor either free of obstruction so as not to impede the flow of water or constructed with non-supporting breakaway walls, open wood lattice-work, or insect screening intended to collapse under wind and water loads without causing collapse, displacement, or other structural damage to the elevated portion of the building or supporting foundation system. All breakaway walls shall be constructed according to structural designs, plans and specifications conforming with ASCE 24 Chapter 4, signed by a licensed design professional,

and certified by that individual in a Breakaway Wall Certificate. Prior to construction, plans for breakaway walls must be submitted to the Code Enforcement Official for approval.

- i. Any alteration, repair, reconstruction or improvement to a structure started after the enactment of this chapter shall not enclose the space below the lowest floor unless breakaway walls, open wood latticework or insect screening are used as provided for in this section.
- ii. Except in the Flood Hazard Protection Area – Primary Frontal Dune,, breakaway walls, open wood lattice work or insect screening shall be allowed below the base flood elevation, provided that they are intended to collapse under wind and water loads without causing collapse, displacement or other structural damage to the elevated portion of the building or supporting foundation system. Breakaway walls shall be designed for a safe loading resistance of not less than 10 and no more than 20 pounds per square foot. Use of breakaway walls which exceed a design safe loading of 20 pounds per square foot (either by design or when so required by local or state codes) may be permitted only if a licensed design professional certifies that the designs proposed meet the following conditions:
  1. Breakaway wall collapse shall result from a water load less than that which would occur during the base flood and,
  2. The elevated portion of the building and supporting foundation system shall not be subject to collapse, displacement or other structural damage due to the effects of wind and water load acting simultaneously on all building components (structural and nonstructural). Water loading values used shall be those associated with the base flood. Wind loading values used shall be those required by applicable state or local building standards.
- e. Enclosures - All new construction and substantial improvements with fully enclosed areas below the lowest floor shall be used solely for parking of vehicles, building access, or storage in an area other than a basement and which are subject to flooding. Enclosures shall:
  - i. Be constructed using breakaway walls.
  - ii. Be situated at or above the adjoining exterior grade along at least one entire exterior wall, in order to provide positive drainage of the enclosed area in accordance with N.J.A.C. 7:13; enclosures (including crawlspaces and basements) which are below grade on all sides are prohibited.

- iii. Be designed to automatically equalize hydrostatic flood forces on exterior walls by allowing for the entry and exit of floodwaters unless the structure is non-residential and the requirements of 94-15.2(2)(d)ii are met;
  - iv. Be constructed to meet the requirements of ASCE 24 Chapter 4;
  - v. Have openings documented on an Elevation Certificate and have breakaway wall construction documented on a Breakaway Wall Certificate unless the requirements of 94-15.2(2)(d)ii are met for a non-residential structure; and
  - vi. Have documentation that a deed restriction has been obtained for the lot if the enclosure is greater than six feet in height. This deed restriction shall be recorded in the Office of the County Clerk or the Registrar of Deeds and Mortgages in which the building is located, shall conform to the requirements in N.J.A.C.7:13, and shall be recorded within 90 days of receiving a Flood Hazard Area Control Act permit or prior to the start of any site disturbance (including pre-construction earth movement, removal of vegetation and structures, or construction of the project), whichever is sooner. Deed restrictions must explain and disclose that:
    - 1. The enclosure is likely to be inundated by floodwaters which may result in damage and/or inconvenience.
    - 2. The depth of flooding that the enclosure would experience to the Flood Hazard Area Design Flood Elevation.
    - 3. The deed restriction prohibits habitation of the enclosure and explains that converting the enclosure into a habitable area may subject the property owner to enforcement.
- f. Specifications for concrete slab construction
- i. Except for the Flood Hazard Protection Area – Primary Frontal Dune, all slabs shall be a minimum of one foot above the crown of the road or easement upon which the structure being serviced by such slab is located. Any building or structure which had a concrete slab below the elevation as required by this chapter prior to October 29, 2012, may have the concrete slab replaced at the elevation at which it existed prior to October 29, 2012, provided that the construction is not

considered a substantial improvement subject to elevation to the Local Design Flood Elevation.

- ii. In the Flood Hazard Protection Area – Primary Frontal Dune, any existing building or structure which has a concrete slab lower than 14 feet above mean sea level and/or below grade is permitted only for use as a garage, a storage area, or an entrance foyer provided that the structure has not been substantially improved. At substantial improvement, any below-grade areas must be mitigated and the property must be made compliant with this Chapter.

All slab floors shall be a monolithic pour with the perimeter no more than 10 inches thick for a distance of six inches from the edge of the pour with the balance of the monolithic pour being four inches thick. No such slab shall contain wire mesh, rebar, or other supporting membrane other than fiber mesh.

- iii. All new and substantially improved building or structures shall have the bottom of any slab placed above grade and at a minimum elevation of 14 feet NAVD88.

g. Special Construction Requirements in the Flood Hazard Protection Area – Primary Frontal Dune

- i. Any building or structure in the beach dune area shall have a maximum building height as required by § 205-10 of the Code of Long Beach Township.
- ii. The primary living level/lowest floor shall be supported by pilings and a horizontal structural member parallel to the flow of water.
- iii. All space below the primary living level/lowest floor shall have exterior breakaway wall construction as required by this Chapter. However, breakaway walls shall not be permitted to extend below grade, the base flood elevation, or the elevation required by §§ 51-3 and 51-5 of the Code of the Township of Long Beach.
  - 1. Compliance with all structural support requirements as set forth in this subsection shall be certified to by a New Jersey Licensed Professional Engineer.

h. Structural Support

- i. All new construction and substantial improvements shall be elevated on piling or columns.
- ii. The pilings or column foundations and all structures attached thereto shall be anchored to resist flotation, collapse or lateral movement due to the effective wind- and water-loading values, each of which shall have a one-percent chance of being equal or exceeded in any given year (one-hundred-year mean recurrence interval).
- iii. There shall be no fill used for any structural support in any V Zone.
  1. All pilings shall have a minimum diameter of 10 inches and shall be driven or jetted so that the lowest point of such pilings shall be 10 feet below sea level as determined by the 1988 North America Vertical Datum. If any such pilings are jetted, they must be driven to resistance.
  2. Any wood and pilings installed at grade or below designated flood elevations shall be appropriately pressure preserved to meet the standards of AWWPA (American Wood-Preservers' Association) U1 for the species, product, preservative, and end use of the material. Plywood shall be preservative treated in accordance with AWWPA (American Wood-Preservers' Association) standard C9-3 with creosote, pentachlorophenol preservatives, or equivalent.
  3. Compliance with all structural support requirements as set forth in this Section shall be certified to by a New Jersey Licensed Professional Engineer.
  4. A licensed design professional shall develop or review the structural design specifications and plans for the construction and shall certify that the design and methods of construction to be used are in accordance with accepted standards of practice for compliance with the provisions of this Chapter and that all new construction and substantial improvements in the oceanfront VE Zone shall be securely anchored on pilings and all new construction and substantial improvements in the VE Zone-II shall be securely anchored on pilings or columns.



**94-15.3 Garages and accessory storage structures.** Garages and accessory storage structures shall be designed and constructed in accordance with the Uniform Construction Code.

**94-15.4 Fences.** Fences in floodways that have the potential to block the passage of floodwater, such as stockade fences and wire mesh fences, shall meet the requirements of Section 94-5.3(1) of these regulations. Pursuant to N.J.A.C. 7:13, any fence located in a floodway shall have sufficiently large openings so as not to catch debris during a flood and thereby obstruct floodwaters, such as barbed-wire, split-rail, or strand fence. A fence with little or no open area, such as a chain link, lattice, or picket fence, does not meet this requirement. Foundations for fences greater than 6 feet in height must conform with the Uniform Construction Code. Fences for pool enclosures having openings not in conformance with this section but in conformance with the Uniform Construction Code to limit climbing require a variance as described in Section 94-7 of this ordinance.

**94-15.5 Retaining walls, sidewalks, and driveways.** Retaining walls, sidewalks and driveways that involve placement of fill in floodways shall meet the requirements of Section 94-5.3(1) of these regulations and N.J.A.C. 7:13.

**94-15.6 Swimming pools.** Swimming pools shall be designed and constructed in accordance with the Uniform Construction Code. Above-ground swimming pools and below-ground swimming pools that involve placement of fill in floodways shall also meet the requirements of Section 94-5.3(1) of these regulations. Above-ground swimming pools are prohibited in floodways by N.J.A.C. 7:13.

**94-15.7 Roads and watercourse crossings.**

- (1) For any railroad, roadway, or parking area proposed in a flood hazard area, the travel surface shall be constructed at least one foot above the Flood Hazard Area Design Elevation in accordance with N.J.A.C. 7:13.
- (2) Roads and watercourse crossings that encroach into regulated floodways or riverine waterways with base flood elevations where floodways have not been designated, including roads, bridges, culverts, low- water crossings and similar means for vehicles or pedestrians to travel from one side of a watercourse to the other side, shall meet the requirements of Section 94-5.3(1) of these regulations.

**94-15.8 Other development in coastal high hazard areas (Zone V) and Coastal A Zones.** In Coastal High Hazard Areas (V Zones) and Coastal A Zones, development activities other than buildings and structures shall be permitted only when also authorized by the appropriate Federal, State or local authority; when located outside the footprint of, and not structurally attached to, buildings and structures; and when analyses prepared by a licensed professional engineer demonstrates no harmful diversion of floodwater or wave runup and wave reflection that would increase damage to adjacent buildings and structures. Such other development activities include but are not limited to:

- (1) Bulkheads, seawalls, retaining walls, revetments, and similar erosion control structures;

- (2) Solid fences and privacy walls, and fences prone to trapping debris, unless designed and constructed to fail under flood conditions less than the base flood or otherwise function to avoid obstruction of floodwater; and
- (3) On-site filled or mound sewage systems.

**94-15.9 Nonstructural fill in coastal high hazard areas (Zone V) and Coastal A Zones.** In coastal high hazard areas and Coastal A Zones:

- (1) Minor grading and the placement of minor quantities of nonstructural fill shall be permitted for landscaping and for drainage purposes under and around buildings.
- (2) Nonstructural fill with finished slopes that are steeper than one unit vertical to five units horizontal shall be permitted only when an analysis prepared by a licensed professional engineer demonstrates no harmful diversion of floodwater or wave runup and wave reflection that would increase damage to adjacent buildings and structures.
- (3) Sand dune construction and restoration of sand dunes under or around elevated buildings are permitted without additional engineering analysis or certification of the diversion of floodwater or wave runup and wave reflection where the scale and location of the dune work is consistent with local beach-dune morphology and the vertical clearance is maintained between the top of the sand dune and the lowest horizontal structural member of the building.

**SECTION 94-16 TEMPORARY STRUCTURES AND TEMPORARY STORAGE**

**94-16.1 Temporary structures.** Temporary structures shall be erected for a period of less than 180 days. Temporary structures shall be anchored to prevent flotation, collapse or lateral movement resulting from hydrostatic loads, including the effects of buoyancy, during conditions of the base flood. Fully enclosed temporary structures shall have flood openings that are in accordance with ASCE 24 to allow for the automatic entry and exit of flood waters.

**94-16.2 Temporary storage.** Temporary storage includes storage of goods and materials for a period of less than 180 days. Stored materials shall not include hazardous materials.

**94-16.3 Floodway encroachment.** Temporary structures and temporary storage in floodways shall meet the requirements of Section 94-5.3(1) of these regulations.

**SECTION 94-17 UTILITY AND MISCELLANEOUS GROUP U**

**94-17.1 Utility and Miscellaneous Group U.** In accordance with Section 312 of the International Building Code, Utility and Miscellaneous Group U includes buildings and structures that are accessory in character and miscellaneous structures not

classified in any specific occupancy in the Building Code, including, but not limited to, agricultural buildings, aircraft hangars (accessory to a one- or two-family residence), barns, carports, communication equipment structures (gross floor area less than 1,500 sq. ft.), fences more than 6 feet (1829 mm) high, grain silos (accessory to a residential occupancy), livestock shelters, private garages, retaining walls, sheds, stables, tanks and towers.

- 94-17.2 Flood loads.** Utility and miscellaneous Group U buildings and structures, including substantial improvement of such buildings and structures, shall be anchored to prevent flotation, collapse or lateral movement resulting from flood loads, including the effects of buoyancy, during conditions up to the Local Design Flood Elevation as determined in Section 94-2.3.
- 94-17.3 Elevation.** Utility and miscellaneous Group U buildings and structures, including substantial improvement of such buildings and structures, shall be elevated such that the lowest floor, including basement, is elevated to or above the Local Design Flood Elevation as determined in Section 94-2.3 and in accordance with ASCE 24. Utility lines shall be designed and elevated in accordance with N.J.A.C. 7:13.
- 94-17.4 Enclosures below base flood elevation.** Fully enclosed areas below the design flood elevation shall be constructed in accordance with Section 94-15.2 and with ASCE 24 for new construction and substantial improvements. Existing enclosures such as a basement or crawlspace having a floor that is below grade along all adjoining exterior walls shall be abandoned, filled-in, and/or otherwise modified to conform with the requirements of N.J.A.C. 7:13 when the project has been determined to be a substantial improvement by the Floodplain Administrator.
- 94-17.5 Flood-damage resistant materials.** Flood-damage-resistant materials shall be used below the Local Design Flood Elevation determined in Section 94-2.3.
- 94-17.6 Protection of mechanical, plumbing, and electrical systems.** Mechanical, plumbing, and electrical systems, equipment and components, heating, ventilation, air conditioning, plumbing fixtures, duct systems, and other service equipment, shall be elevated to or above the Local Design Flood Elevation determined in Section 94-2.3.
- Exception:** Electrical systems, equipment and components, and heating, ventilating, air conditioning, and plumbing appliances, plumbing fixtures, duct systems, and other service equipment shall be permitted to be located below the Local Design Flood Elevation provided that they are designed and installed to prevent water from entering or accumulating within the components and to resist hydrostatic and hydrodynamic loads and stresses, including the effects of buoyancy, during the occurrence of flooding to the Local Design Flood Elevation in compliance with the flood-resistant construction requirements of ASCE 24. Electrical wiring systems shall be permitted to be located below the Local Design Flood Elevation provided they conform to the provisions of NFPA 70 (National Electric Code).

### **SECTION 3. SEVERABILITY.**

Where any section, subsection, sentence, clause, or phrase of these regulations is, for

any reason, declared by the courts to be unconstitutional or invalid, such decision shall not affect the validity of the regulations as a whole, or any part thereof, other than the part so declared.

**SECTION 4. EFFECTIVE DATE.**

This ordinance shall take effect on **December 16, 2021**

*[Jurisdiction to add signature blocks.]*

**NOTICE**

Public Notice is hereby given that the foregoing Ordinance 21-32C was introduced and passed on the first reading at a regular meeting of the Board of Commissioners of the Township of Long Beach, County of Ocean, State of New Jersey, held on Monday, November 1, 2021, at 4:00 p.m.

Further public notice is hereby given that said ordinance shall be considered for final passage and adoption at a regular meeting of the Board of Commissioners to be held on Monday, December 6, 2021, at 4:00 p.m. at the Public Safety Building, 6805 Long Beach Blvd., Brant Beach, NJ 08008.

---

**Danielle La Valle, RMC**  
Municipal Clerk

First Reading: November 1, 2021  
Publication: November 4, 2021  
Second Reading: December 6, 2021  
Final Publication: December 9, 2021  
Effective: December 9, 2021

**CERTIFICATION**

**I, DANIELLE LA VALLE, RMC**, Municipal Clerk for the Township of Long Beach do hereby certify that the foregoing Ordinance 21-32C was duly adopted by the Board of Commissioners at their meeting held on Monday, December 6, 2021, at 4:00 p.m.

---

Danielle La Valle, RMC  
Municipal Clerk

First Reading: November 1, 2021  
Publication: November 4, 2021  
Second Reading: December 6, 2021  
Final Publication: December 9, 2021  
Effective: December 9, 2021